For more assistance with technical questions please call our technical support staff at (714) 259-9959. You can also contact us by email at info@brucklightingsystems.com.

BRUCK

INSTALLATION AND WIRING DIAGRAM


FLIGHT

VERTICAL FLUSH MOUNT SUPPORT

ART. NO. 225 010mc

Â

matte chrome, vertical



Â

IMPORTANT SAFETY INSTRUCTIONS

- 1. SAVE THESE INSTRUCTIONS AND REFER TO THEM WHEN ADDITIONS TO OR CHANGES IN THE TRACK CONFIGURATION ARE MADE.
- 2. THIS PRODUCT MUST BE INSTALLED BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED, IN ACCORDANCE WITH LOCAL AND NATIONAL CODE.
- 3. Do not install this track in Damp or Wet locations.
- 4. Do not install any part of the track less than 7 feet above the floor.
- 5. Do not install any fixture assembly closer than 6 inches from any curtain, or similar combustible material.
- 6. Turn off power prior to any work on the systems.
- 7. Do not attempt to energize anything other than lighting track fixtures specified for use with the FLIGHT system. To reduce the risk of fire and electric shock, do not attempt to connect power tools, extension cords, appliances, and the like to the track.
- 8. This track system MUST BE HARD WIRED. For all the wire connections, use Listed Wire Nuts.
- 9. Total wattage of the system must never exceed 300W or wattage supplied by the low-voltage transformer.
- 10. Secondary connections must be clean and tight to avoid arcing and overheating!
- 11. Warranty is void in case of unauthorized modifications and/ or improper use.

READ ALL OF THESE INSTALLATION INSTRUCTIONS BEFORE INSTALLING THE FIXTURE

Contents of Delivery: FLIGHT VERTICAL FLUSH MOUNT SUPPORT - qty. (1)

Note

The track should be bent into its desired shape prior to mounting any supports so that the mounting positions can be marked on the ceiling. Supports should be mounted approximately every three feet.

Step 1.

- Unscrew the mounting base (A) from the support (B) and insert mounting screw (C) to attach to the ceiling base. Screw the support back onto the mounting base.

- Slide the Flight track (D) into the groove of the support (B). Tighten the set screw (E) firmly to secure the track.

