



Description:

The Bling II Down MP2 pendant includes a 2" kiss mono-point canopy with integral 2" J-box and 75 Watt transformer. Standard cable length of 59" can be field-cut or specified when ordering. May be specified with 4" kiss mono-point canopy by adding /MP to the part number.

Part Numbers:

220174bz/MP2	bronze, amber glass
220174ch/MP2	chrome, amber glass
220174mc/MP2	matte chrome, amber glass
220179bz/MP2	bronze, white glass
220179ch/MP2	chrome, white glass
220179mc/MP2	matte chrome, white glass
221843bz/MP2	bronze, black glass
221843ch/MP2	chrome, black glass
221843mc/MP2	matte chrome, black glass
221844bz/MP2	bronze, gold glass
221844ch/MP2	chrome, gold glass
221844mc/MP2	matte chrome, gold glass
221845bz/MP2	bronze, silver glass
221845ch/MP2	chrome, silver glass
221845mc/MP2	matte chrome, silver glass

Technical Specs:

- 120V AC, 50/60Hz input
- 11.7V AC output
- 50VA, 49W for 1 (maximum 50 Watt lamp)
- GY6.35 socket
- Suitable for dry locations only
- 2 1/4" hole cutout
- Required material thickness 3/16" - 1 1/16"
- Not thru-wire rated
- Short circuit protection
- Overload protection
- Thermal protection
- Dimmable
- May also be specified with MR16 socket