



Description:

The Ciro Down MP2 pendant includes a 2" kiss mono-point canopy with integral 2" J-box and 75 Watt transformer. Standard cable length of 59" can be field-cut or specified when ordering. May be specified with 4" kiss mono-point canopy by adding /MP to the part number.

Part Numbers:

220116bz/MP2	bronze, yellow and red glass
220116ch/MP2	chrome, yellow and red glass
220116mc/MP2	matte chrome, yellow and red glass
220119bz/MP2	bronze, white fritted glass
220119ch/MP2	chrome, white fritted glass
220119mc/MP2	matte chrome, white fritted glass
220121bz/MP2	bronze, gold-leaf glass
220121ch/MP2	chrome, gold-leaf glass
220121mc/MP2	matte chrome, gold-leaf glass
220122bz/MP2	bronze, red glass
220122ch/MP2	chrome, red glass
220122mc/MP2	matte chrome, red glass
220123bz/MP2	bronze, lava glass
220123ch/MP2	chrome, lava glass
220123mc/MP2	matte chrome, lava glass
220124bz/MP2	bronze, tan mosaic glass
220124ch/MP2	chrome, tan mosaic glass
220124mc/MP2	matte chrome, tan mosaic glass
220125bz/MP2	bronze, red mosaic glass
220125ch/MP2	chrome, red mosaic glass
220125mc/MP2	matte chrome, red mosaic glass

Technical Specs:

120V AC, 50/60Hz input
 11.7V AC output
 50VA, 49W for 1 (maximum 50 Watt lamp)
 GY6.35 socket
 Suitable for dry locations only
 2 1/4" hole cutout
 Required material thickness 3/16" - 1 1/16"
 Not thru-wire rated
 Short circuit protection

Overload protection
Thermal protection
Dimmable