

**Replacement Parts:**

|            |              |
|------------|--------------|
| LED Module | LED-0124/830 |
| LED Driver | 75951        |
| Glass Lens | 140902       |

CSA certified to U.S. and Canadian standards. Suitable for wet locations.

Protection Class: IP67

Weight: 1.9 lbs.



**Dimensions**

- A: 4-3/8"
- B: 2-3/4"
- C: 4-3/4"



**Luminaire 7010LED:**

**Housing:** Reinforced polyimide synthetic housing for maximum corrosion resistance. Reflector made of pure anodized aluminum. Clear safety glass. Stainless steel trim ring. Flush installation with ground suitable for foot traffic.

**Note: Not suitable for drive-over applications.**

**Electrical:** 4.5W LED luminaire, 6 total system watts, -30°C start temperature. Integral 12V AC driver provided. Standard LED color temperature is 3000K with an 83 CRI.

**IMPORTANT: For use with magnetic landscape transformers ONLY.**

**Warranty:** 3 year manufacturer warranty.

**Notice to Installer for 7010LED:**

**WARNING:** LEDs are high quality electrical components. Please avoid opening upper electrical compartment and do NOT touch LED module.

1. Compatible for use with 12-24V AC input voltage.
2. Voltage must NOT drop below 10V.
3. Turn main power OFF before start of installation.

**7010LED installation:**

1. Establish planned fixture location and provide supply wiring.
2. Intended for installation in soil, sod, or gravel.
3. Dig hole at least 5" deep for luminaire.  
 Recommended: Provide an additional 6" of pea gravel or similar underneath luminaire to facilitate water drainage.
4. Make wiring connections. For maximum wire run lengths, see table below.
5. Fill soil or gravel around luminaire assuring housing stays level.

**Lamp:** Integral 4.5W LED Module  
(No replacement necessary)

| Max. Run Length (ft) Per Wire Size: 2 Volt drop |                 |     |     |      |      |
|---|-----------------|-----|-----|------|------|
| Connected LED Watts                             | Wire Size (AWG) |     |     |      |      |
|   | 18              | 16  | 14  | 12   | 10   |
| 40  | 46              | 73  | 116 | 185  | 294  |
| 30  | 61              | 97  | 155 | 246  | 392  |
| 20  | 92              | 146 | 232 | 369  | 588  |
| 15  | 122             | 195 | 309 | 492  | 784  |
| 10  | 183             | 292 | 464 | 738  | 1176 |
| 5   | 366             | 585 | 928 | 1477 | 2353 |

In the interest of product improvement, BEGA reserves the right to make technical changes without notice.