

VBLFL-83x-4-C



Applications:

- Warehouses
- Caravan Parks
- Hotels
- Supermarkets
- Gardens
- Walk ways
- Exhibition Centres
- Museums
- Commercial Building
- Industrial Buildings

Features:

- IP65 Rated
- 120° Beam Angle
- Low Wattages
- Long Life of 50,000 hours



RGB Range:

Model Number	VBLFL-832-4-C	VBLFL-833-4-C	VBLFL-834-4-C	VBLFL-836-4-C
Wattage	10W	20W	30W	50W
Input Voltage	AC85-265V	AC85-265V	AC85-265V	AC85-265V
Output Voltage	R: 6-8V 290mA G: 9-12V 290mA B: 9-12V 290mA	R: 6-8V 290mA G: 9-12V 290mA B: 9-12V 290mA	R: 6-8V 290mA G: 9-12V 290mA B: 9-12V 290mA	R: 6-8V 290mA G: 9-12V 290mA B: 9-12V 290mA
HZ	50-60Hz	50-60Hz	50-60Hz	50-60Hz
LED Source	Epistar	Epistar	Epistar	Epistar
Beam Angle	120°	120°	120°	120°
IP Rating	IP65	IP65	IP65	IP65
Lamp Life	50,000 hours	50,000 hours	50,000 hours	50,000 hours
Dimension (mm)	155 x 105 x 90	180 x 140 x 110	225 x 183 x 130	290 x 240 x 150
Weight per Item	1.5kg	1.8kg	2.6kg	3.5kg
Power Supply	LF22010WRGB	LF22020WRGB	LF22030NW	LF22050RGB
Safety Certificates	CE & SAA	CE & SAA	CE & SAA	CE & SAA
Warranty	3 years	3 years	3 years	3 years



RGB Floodlight Remote Control

Average Lux Levels for White:

