



Contemporary  
Lighting™

Product Specifications for E63007-11

Job Name:	Job Type:
Quantity:	Comments:



**E63007-11**  
Cilandro 2-Light CFL Wall Mount

**Finish**  
Satin Nickel

**Glass/Shade**  
Matte White

**Product Category**  
Bath Vanity

**Lamping**

Number of Bulb(s)	2
Light Type	Fluorescent
Bulb Type	GX23-2 T4
Max Bulb Wattage	13
Max Fixture Wattage	26
Rated Life	±10,000 Hours
Rated Lumens	±1,560
Color Temp	±2,700 K
Bulb(s) Included	Yes
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast	N/A

**Measurements**

Width	4.50"
Height	19.00"
Length	N/A
Extension	4.00"
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	N/A
Hanging Weight	N/A
Height Adjustable	N/A
Slope	N/A

**Shipping**

Carton Weight	1.66 lb(s)
Carton Width	7.00"
Carton Height	7.50"
Carton Length	30.50"
Carton Cubic Feet	N/A
Master Pack	4
Master Pack Weight	22.00 lb(s)
Master Pack Width	17.50"
Master Pack Height	18.00"
Master Pack Length	17.50"
Master Cubic Feet	N/A
UPS Shippable	Yes

**Certification**

UL/ETL/CSA	Damp
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	Yes

**Other**

UPC Code	845094016878
Material	N/A

**Equivalents**

Incandescent Watts	N/A
Fluorescent Watts	N/A

ET2 Contemporary Lighting and all designs, logos and images © 2010 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Products are subject to revision in design and/or construction to conform to changes in UL and/or CSA and/or ETL standards, or that which may be required by law or availability of material. ET2 Contemporary Lighting products are UL, ETL or CSA approved. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.