

Contemporary Lighting™

## Product Specifications for E63006-11

Job Name:	Job Type:
Quantity:	Comments



E63006-11 Cilandro 1-Light CFL Wall Mount

**Product Category** 

4.90 lb(s)

7.00"

6.50"

19.50"

N/A

N/A

15.00"

13.50"

20.00"

N/A

Yes

4

Bath Vanity

*Finish* Satin Nickel

## Lamping

Lamping	
Number of Bulb(s)	1
Light Type	Fluorescent
Bulb Type	G24q-2 T4
Max Bulb Wattage	18
Max Fixture Wattage	18
Rated Life	±10,000 Hours
Rated Lumens	±1,250
Color Temp	±2,700 K
Bulb(s) Included	Yes
Light Up/Down	N/A
Beam Spread	N/A
CRI	N/A
Photo Cell Included	N/A
Ballast	N/A

## Glass/Shade Matte White

**Measurements** Shipping Carton Weight Width 4.50" Height 12.00" Carton Width Length N/A Carton Height Extension 4.00" Carton Length **Back Plate Width** N/A Carton Cubic Feet **Back Plate Height** N/A Master Pack HCO N/A Master Pack Weight Min Overall Height N/A Master Pack Width Max Overall Height N/A Master Pack Height Hanging Weight 0.93 lb(s) Master Pack Length N/A Master Cubic Feet **Height Adjustable** Slope N/A UPS Shippable

Certification		Other		Equivalents	
UL/ETL/CSA	Damp	UPC Code	845094016861	Incandescent Watts	N/A
Energy Star	No	Material	N/A	Fluorescent Watts	N/A
CA Title 24	No				
CA Title 20	No				
ADA	Yes				

ET2 Contemporary Lighting and all designs, logos and images © 2010 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Products are subject to revision in design and/or construction to conform to changes in UL and/or CSA and/or ETL standards, or that which may be required by law or availability of material. ET2 Contemporary Lighting products are UL, ETL or CSA approved. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.