

Product	Specifications	for	F94641	-113SN
1 IOGGC	Opcomodions	101		11001

Job Name:	Јоб Туре:
Quantity:	Comments



E94641-113SN

Minx 3-Light RapidJack Pendant and Canopy

Finish Satin Nickel

Glass/Shade White Cirrus

Other

Product Category Multi-Light Pendant

Lamping

Light Type Xenon Bulb Type 12V G4 Max Bulb Wattage 35 Max Fixture Wattage 105 Rated Life ±2,000 Hours Rated Lumens ±1,770 Color Temp ±2,900 K Bulb(s) Included Yes Light Up/Down N/A Beam Spread N/A CRI N/A Photo Cell Included N/A Ballast/Driver/Transformer Yes	=amping	
Bulb Type 12V G4 Max Bulb Wattage 35 Max Fixture Wattage 105 Rated Life ±2,000 Hours Rated Lumens ±1,770 Color Temp ±2,900 K Bulb(s) Included Yes Light Up/Down N/A Beam Spread N/A CRI N/A Photo Cell Included N/A Ballast/Driver/Transformer Yes	Number of Bulb(s)	3
Max Bulb Wattage 35 Max Fixture Wattage 105 Rated Life ±2,000 Hours Rated Lumens ±1,770 Color Temp ±2,900 K Bulb(s) Included Yes Light Up/Down N/A Beam Spread N/A CRI N/A Photo Cell Included N/A Ballast/Driver/Transformer Yes	Light Type	Xenon
Max Fixture Wattage 105 Rated Life ±2,000 Hours Rated Lumens ±1,770 Color Temp ±2,900 K Bulb(s) Included Yes Light Up/Down N/A Beam Spread N/A CRI N/A Photo Cell Included N/A Ballast/Driver/Transformer Yes	Bulb Type	12V G4
Rated Life ±2,000 Hours Rated Lumens ±1,770 Color Temp ±2,900 K Bulb(s) Included Yes Light Up/Down N/A Beam Spread N/A CRI N/A Photo Cell Included N/A Ballast/Driver/Transformer Yes	Max Bulb Wattage	35
Rated Lumens ±1,770 Color Temp ±2,900 K Bulb(s) Included Yes Light Up/Down N/A Beam Spread N/A CRI N/A Photo Cell Included N/A Ballast/Driver/Transformer Yes	Max Fixture Wattage	105
Color Temp ±2,900 K Bulb(s) Included Yes Light Up/Down N/A Beam Spread N/A CRI N/A Photo Cell Included N/A Ballast/Driver/Transformer Yes	Rated Life	±2,000 Hours
Bulb(s) Included Yes Light Up/Down N/A Beam Spread N/A CRI N/A Photo Cell Included N/A Ballast/Driver/Transformer Yes	Rated Lumens	±1,770
Light Up/Down N/A Beam Spread N/A CRI N/A Photo Cell Included N/A Ballast/Driver/Transformer Yes	Color Temp	±2,900 K
Beam Spread N/A CRI N/A Photo Cell Included N/A Ballast/Driver/Transformer Yes	Bulb(s) Included	Yes
CRI N/A Photo Cell Included N/A Ballast/Driver/Transformer Yes	Light Up/Down	N/A
Photo Cell Included N/A Ballast/Driver/Transformer Yes	Beam Spread	N/A
Ballast/Driver/Transformer Yes	CRI	N/A
	Photo Cell Included	N/A
Dimmable Low-Voltage	Ballast/Driver/Transformer	Yes
	Dimmable	Low-Voltage

8.4			ire			.4-
IVI	$\boldsymbol{\rho}$	SI	IFP	m	er	ITS

Measurents	
Width	11.75"
Height	7.00"
Length	N/A
Extension	N/A
Back Plate Width	N/A
Back Plate Height	N/A
HCO	N/A
Min Overall Height	N/A
Max Overall Height	128.25"
Hanging Weight	N/A
Height Adjustable	Yes
Slope	N/A
Chain Length	N/A
Wire Length	180.00"
Canopy Width	11.8"
Canopy Height	1.3"
Canopy Length	

Chinning

Shipping	
Carton Weight	N/A
Carton Width	N/A
Carton Height	N/A
Carton Length	N/A
Carton Cubic Feet	N/A
Master Pack	1
Master Pack Weight	N/A
Master Pack Width	N/A
Master Pack Height	N/A
Master Pack Length	N/A
Master Cubic Feet	N/A
UPS Shippable	Yes

Certification

Safety Rating	Dry
Energy Star	No
CA Title 24	No
CA Title 20	No
ADA	No

Equivalents

UPC Code	845094052098	Incandescent Watts	N/A
Material	N/A	Fluorescent Watts	N/A

ET2 Contemporary Lighting and all designs, logos and images © 2013 ET2 Contemporary Lighting. All Rights Reserved. ET2 Contemporary Lighting reserves the right, at any time, to make changes in the design and/or construction of the product including the discontinuation of product without prior notice. Color may vary from what is pictured above due to limitations inherent to photographic processes. Always consult a qualified, licensed electrician before installation of any product weighing 35 pounds or more. We recommend that a qualified, licensed electrician do the installation. Always install to a mechanically sound structure.