



This living room features 13" and 6.5" tiles. Color 100 beige installed in a modular pattern.

Shaw Tile & Stone™
shawfloors.com

Ravenna | *porcelain tile*

Ravenna


Features

- Randomly screened Rotary glazing technique creates realistic and unique stone looks
- High variation and deep contrast gives incredible depth and visual texture
- Designed and Crafted in Italy

Colors



100 Beige



200 Almond




700 Noce


Mosaic



100 Beige



200 Almond



700 Noce

Accent



Insert



Listello



Liner

Tile Sizes

Field Tile	Style
13" x 13"	CS73A
20" x 20"	CS74A
6.5" x 6.5"	CS75A

Trim

3" x 13"	Bullnose	CS77B
2" x 6.5"	Chair Rail	CS78B
2" x 2"	Chair Rail Corner	CS79B
.78" x 6.5"	Quarter Round	CS82B
.79" x .79"	Quarter Beak	CS83B

Accent

2" x 2"	Insert	CS81B
2" x 6.5"	Listello	CS84B
13" x 13"	Mosaic	CS80A
.67" x 6.5"	Pencil Liner	CS80B

Technical

Wear Rating Group	4
Break Strength	309 lbs.
Water Absorption	<.5%
COF (Wet)	.66

This tile features random variations of shade and texture within each carton.

To insure optimum appearance, it is imperative that tiles from various cartons be continually blended during installation. Placement of tiles should be decided on before beginning installation.

*OSHA (Occupational Safety and Health Administration) has established a recognized industry standard of 0.5 (wet and dry) for slip-resistant surfaces. The Americans with Disabilities Act (ADA) recommends, but does not require, "a Static Coefficient of Friction of 0.60 for accessible routes and 0.80 for ramps." ADA does not specifically state that 0.60 is both a dry and a wet requirement. It is important to note that any tile or other hard surface flooring can become slippery when wet or improperly maintained. Products installed in an exterior application must comply with applicable ANSI 108 series of the "American National Standard Specifications for the Installation of Ceramic Tile" and comply with TCA installation methods applicable to installation conditions.

Approved Usage

