



# Monticello Cherry — SW184

Superior **craftsmanship**. Artisans achieve the venerable look of **antiquity** by scraping each lushly **grained** plank by hand.

color 945 jefferson cherry

Green. It's something we never forget. That's the Shaw Green Edge I™



### **PRODUCT INFORMATION & SPECIFICATIONS**

Shaw Industries, Inc. PO Drawer 2128 Mail Drop 02601 Dalton, GA 30722-2128 I-800-441-7429 shawfloors.com

## **Specifications**

style	Monticello Cherry <b>sw184</b>
construction	engineered
length	random 10" to 581/2"
thickness x width	3/8" × 5"
species	cherry
edge description	microbeveled edges and ends
warranty	now & forever lifetime wear
installation method	glue/staple/nail/float

Note: All woods are affected by light. Some exotic species will darken while other species will tend to lighten over a period of time when exposed to natural and artificial light sources. Some wood species darken and/or lighten at a faster rate than others. This is a natural characteristic of wood and does not constitute any type of product defect.

# SHAW GREEN EDGE<sup>™</sup>

Epic's 3/8" thick hardwood products use approximately 50% less newly forested wood in their production than conventional 3/8" engineered alternatives. That's the Shaw Green Edge

#### **Key Selling Features**



Shaw warrants to the original purchaser that the face surface of this engineered hardwood product will not peel off or wear through for as long as you own your home.



Shaw hardwood is labeled with a Color Variation Rating to distinguish the degree of color variation within each box of flooring and between several boxes of the same color. This hardwood is rated CV2 Moderate with distinguishable differences

in color variation. It is imperative that hardwood planks from various cartons be continually blended during installation to insure optimum appearance.



This Shaw product is made in the USA.

#### **Coordinating Trim Pieces**



Flush Reducer SVV895



Overlap Reducer SW896



Overlap Stairnose SW898

Threshold SVV899

shold Q /899

Quarter Round SW901



T-Molding SW900

# Installation Grade

ground level.

This Shaw product can be installed above, on or below



This Shaw hardwood is protected by our DuraShield<sup>™</sup> finish, which provides superior wear resistance and lasts up to seven times longer than conventional UV cured urethane.



This Shaw hardwood is made from an exotic wood species that is considered to be photosensitive. A photosensitive species will darken with exposure to light — a process that enhances the natural beauty of

the species. While most exotic hardwood flooring is maturing, it will develop a deeper, richer color that is noticeably darker than when it was initially installed. This deepening of color is a feature that is inherent to exotic wood species and usually stabilizes within 3-12 months after installation.



This product is made with Shaw's EnviroCore™, a high-density fiber core derived from recycled wood fiber, which means fewer trees are used with less waste.

## SHAW GREEN EDGE INITIATIVE™ I 009

SW897