

HOLSAG CANADA

Seating Manufacturer

Specifications: Bulldog Armchair

Description

The name "Bulldog" represents the sturdy nature of this seating line that includes a side chair, armchair, barstool and matching benches. The side rails are extra thick to support the weight of people climbing up and leaning onto the chair next to them. The back slats are raised from the seat to allow for easy cleaning. Upholstered seats as well as solid wood seats are available. The wood seats are sculpted at the factory to ensure a comfortable sitting position.

Dimensions: Armchair

Height	35"	89 cm
Depth	19"	48 cm
Seat Width	18"	45 cm
Seat Depth	16.5"	42 cm
Seat Height	18"	45 cm
Arms Height	26.5	67 cm
Arms Outside	21.5"	54 cm
Arms Inside	19"	48 cm
Chair Weight	20 lbs	9 kg
Carton Weight		
with 1 chair	30 lbs	13.6 kg
Carton Size		
	18.25" x 24.5" x 37.5"	
	46 cm x 62 cm x 95 cm	
Volume	9.7 cubic feet	

The Bulldog armchair is non-stacking.

Fabric for upholstered seats

COM (Customer's Own Material) fabric required:
.35 yd (.33 m)

Note: This is the estimated amount based on 54" (137 cm) wide material. The actual amount required may vary depending on special pattern matching and the width of the material.

Stock fabric: Black vinyl is available as a stock fabric.

Cushion Foam: High density 1.5" (3.8 cm) thick on seat

Wood

Species: 100% Solid European Beech Hardwood

Construction

Joints: Mortise and tenon.
Glued with high solids glue and reinforced with 18 gauge nails, corner blocks and low root woodscrews.


Stain Colors

A wide range of standard stain colors is available as well as custom color matching. (A surcharge will apply to custom colors.)

9-Step Finishing Process

1. The bare wood of the assembled chair is thoroughly sanded using 120 grit paper.
2. One coat of stain is sprayed onto the entire chair – including the underside of the seat.
3. The stain is handwiped to ensure an even color and maximum penetration into the wood.
4. The chair is inspected and any necessary adjustments made.
5. One coat of a catalyzed sealer is sprayed onto all wood parts to completely seal the wood – including the underside of the seat.
6. Once dry, the sealer is sanded using 320 grit paper.

7. A final sanding is done using Scotch Brite pads to remove any sanding marks.
8. A catalyzed lacquer is sprayed on. This lacquer is very durable and will stand up in a commercial environment.
9. A final inspection is performed prior to packaging to ensure a high level of quality control.



Note: Specifications are subject to change without notice.

Holsag Canada

164 Needham Street
Lindsay, Ontario Canada
K9V 5R7
(705) 878-1970
(888) 745-0721 (U.S. & Canada)
Fax: (705) 878-1864

www.holsag.com