# **Armstrong**

#### **MATERIAL SAFETY DATA SHEET**

Division: Building Products

Date: 3/20/13 (replaces 6/1/12)

N/A = Not applicable or Not Available N/K = None Known or Not Known

Department of Transportation Information

Shipping name: Not Classified

ID No: N/A
Emergency Only Contact: CHEM-TEL 800-255-3924

Hazard Class: N/A

Armstrong World Industries, Inc.

Environment, Health and Safety

2500 Columbia Avenue, P.O. Box 3001

Lancaster, PA 17604

Telephone 1-877-276-7876, Option 3

MSDS: www.armstrong.com

Issued By: Environment, Health and Safety Department

HMIS (0 = minimal hazard, 4 = severe hazard)

 $\begin{aligned} & \text{Health} & = 0 \\ & \text{Flammability} & = 0 \end{aligned}$ 

Reactivity = 0

I. <u>Product Information</u>

A. Product Name: Armstrong MetalWorks Acoustical Ceiling Panels - MSDS #5

N/A

(Includes all MW: Mesh, Open Cell, Plank, Tin, Canopies, RH 200, Wings, Vector, Tegular)

B. Chemical Name and Synonyms : N/A

C. Chemical or Product Family:

II. Ingredient Information

A. Hazardous Components <u>C.A.S No.</u> <u>% OSHA PEL</u> <u>ACGIH TLV</u>

(Chemical Identity; Common Name)

None N/A N/A N/A

These products are electrogalvanized steel and aluminum ceilings. Surface finishes are factory applied and include: unfinished, powder-coated, lacquered or plated. Some perforated panels have a nonwoven acoustical tissue adhered to the back.

These products are classified as an "article" according to Title 29 of the Code of Federal Regulations, OSHA Part 1910.1200(c). They are formed to a specific shape or design during manufacture, have end use functions dependent upon their shape and design, and do not release any hazardous chemical under normal conditions of use.

### III. Physical Data

A. Appearance and Color: Material dependent

B. Boiling Point (degrees F): N/A

C. Vapor pressure ( mm Hg @ 20 degrees C ): N/A

D. Vapor density (Air = 1): N/A

E. Solubility in Water: N/A

F. Specific Gravity ( $H_2O = 1$ ): N/A

G. Percent Volatile by weight (30 min. @ 275 degrees F): N/A

H. Evaporation Rate (Butyl Acetate = 1): N/A

I. pH: N/A

## IV. Fire and Explosion Data

A. Flash point: N/A

B. Flammable Range : LEL = N/A; UEL = N/A

C. Extinguishing Media: Water

D. Special Fire Fighting Procedures: N/A

E. Unusual Fire and Explosion Hazards: None

Continued: Armstrong MetalWorks Acoustical Ceiling Panels - MSDS #5 Date: 3/20/13 (replaces 6/1/12)

## V. Health Data

A. Primary Route (s) of Entry: N/A

B. Target Organs: N/A

Effects of Overexposure: N/A

Skin and Eyes: N/A

Inhalation: N/A

C. Carcinogenicity NTP: No IARC Monographs: No OSHA Regulated: No

D. Medical Conditions Generally aggravated by Exposure: None Known

#### E. First Aid Procedures

Skin and Eyes: N/A Inhalation: N/A

#### VI. Reactivity Data

A. Stability: StableB. Incompatibility: N/K

C. Hazardous decomposition products: None

D. Hazardous Polymerization: Will not occur.

## VII. Spill or Leak Procedures

A. Steps to be taken if material is released or spilled: N/A

B. Waste Disposal method: Dispose in accordance with federal, state and local waste disposal regulations.

## VIII. Special Protection Information

A. Ventilation: N/A

B. Respiratory Protection: None requiredC. Skin and Eye Protection: None required

## IX. Special Precautions

A. Precautions to be taken in handling and storage: N/A

B. Other Precautions: N/K

.....

The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.