



Wide variety of mounting options!



A 250D Pail De-Icer 200 Watts, 120 Volts

- Use in Pails, Pans, or Bird Baths
- Stainless-Steel Guard
- Thermostatically Controlled
- Adjustable Clamp for Mounting
- cULus, CSA Listed

This submersible de-icer features thermostatic control and a stainless-steel guard for safety. An adjustable clamp is included to attach the unit to the container.

B 23ST De-Icer Safety Tether

- Stainless-Steel Construction
- Works With Any De-icer or Stock Tank
- Prevents De-icer from Being Thrown from
- Stainless-Steel Cable

This handy accessory prevents animals from removing your de-icer from the stock tank. It easily fastens through the drain hole of any tank and works with any brand of de-icer.

C 71502 Tankside Heater 1500 Watts, 120 Volts

- User Adjustable and Replaceable Thermostat
- Mounts to Side of Metal Tanks
- Large Heating Element

The Tankside Heater clamps to the side of a metal stock tank. It comes with an adjustable thermostat that allows the user to set the water temperature. This unit takes the place of a deicer by maintaining the water temperature near a set point. The thermostat is replaceable. Not for use in plastic tanks.

D 77 Utility Heater

500 Watts, 120 Volts

- User Adjustable and Replaceable Thermostat
- Heavy Gauge Steel
- Area Heater

This Utility Heater is not immersible but may be used under metal buckets, fountains, or inside various enclosures. It is made of heavygauge steel with an attractive baked-on enamel finish and has an adjustable and replaceable thermostat.

E 742G Bucket Heater 1000 Watts, 120 Volts

- Thermostatically Controlled
- Over-Temperature Protection
- Stainless Steel Heating Element and Guard
- UL, CSA Listed

This unit is designed to heat water as opposed to de-icing water. A stainless-steel guard protects the durable heating element that will heat water past 150°F towards boiling, depending on the bucket's volume and insulation. It comes with a 6 foot cord and is designed to rest easily inside a 5 gallon bucket. The heater is thermostatically controlled with over-temperature protection. For use in water only.

Warranty

All of our products are fully warranted against defects in workmanship for a period of One Year from the date of purchase, unless otherwise noted.



