

# 12"-16" High Speed Cut-Off Wheels - Type 1

## Description and Applications

- AC: (Mix of A/C) – Used on Ductile Iron. 14" are available in both double and triple reinforced.
- C16: Silicon Carbide – Asphalt/Green Concrete
- C24: Silicon Carbide – Stone/Concrete



- **EB – Electronically Balanced.** All 12-14" wheels are automatically balanced during manufacturing. All 12-14" wheels are guaranteed to be less than 3 and 3.5 grams out of balance. CGW wheels are safer, cause less vibration and are more consistent.



- Premium 14" A24R, A24T, AC & 16" wheels are **triple reinforced (TR)** to provide extra safety.



Type 1

12-16" wheels for metal and masonry cutting applications.

## 12-16" AC24-R, Ductile Iron

UPC#	SIZE	SPEC.	RPM	RETAIL PACK	MASTER PACK
<b>35590</b>	12 x 5/32 x 20mm	AC24-R-BF	6,400	10	20
<b>35592</b>	12 x 5/32 x 1	AC24-R-BF	6,400	10	20
<b>36160</b>	14 x 5/32 x 20mm	AC24-R-BF	5,500	10	20
<b>36161</b>	14 x 5/32 x 1	AC24-R-BF	5,500	10	20
<b>35601</b>	14 x 5/32 x 20mm	AC24-R-BF <b>TR</b>	5,500	10	20
<b>35602</b>	14 x 5/32 x 1	AC24-R-BF <b>TR</b>	5,500	10	20
<b>36144</b>	16 x 5/32 x 20mm	AC24-R-BF <b>TR</b>	4,800	10	20
<b>36145</b>	16 x 5/32 x 1	AC24-R-BF <b>TR</b>	4,800	10	20

## 12-16" C24-R, Stone/Concrete

UPC#	SIZE	SPEC.	RPM	RETAIL PACK	MASTER PACK
<b>35596</b>	12 x 5/32 x 20mm	C24-R-BF	6,400	10	20
<b>35598</b>	12 x 5/32 x 1	C24-R-BF	6,400	10	20
<b>35605</b>	14 x 5/32 x 20mm	C24-R-BF	5,500	10	20
<b>35606</b>	14 x 5/32 x 1	C24-R-BF	5,500	10	20
<b>36116</b>	14 x 5/32 x 20mm	C24-R-BF <b>TR</b>	4,400	10	20
<b>36117</b>	14 x 5/32 x 1	C24-R-BF <b>TR</b>	4,400	10	20
<b>36146</b>	16 x 5/32 x 20mm	C24-R-BF <b>TR</b>	4,800	10	20
<b>36147</b>	16 x 5/32 x 1	C24-R-BF <b>TR</b>	4,800	10	20

## 12-14" C16-U, Asphalt/Green Concrete

UPC#	SIZE	SPEC.	RPM	RETAIL PACK	MASTER PACK
<b>35593</b>	12 x 5/32 x 20mm	C16-U-BF	6,400	10	20
<b>35595</b>	12 x 5/32 x 1	C16-U-BF	6,400	10	20
<b>35603</b>	14 x 5/32 x 20mm	C16-U-BF	5,500	10	20
<b>35604</b>	14 x 5/32 x 1	C16-U-BF	5,500	10	20