



I. Product Description

Contact Cleaner and Lubricant is a high purity precision cleaner that replaces CFCs and chlorinated solvent-based cleaners. **Contact Cleaner and Lubricant** cleans surfaces and leaves a fine, microscopic corrosion-proof barrier. Contact Cleaner and Lubricant is safe to use on all plastics and is ideal for outdoor electronics susceptible to moisture and salt air.

II. Applications

Recommended for effective removal of grease, oil and dirt from contacts, circuit breakers, switches, relays, meters, light bulb sockets, control systems and coils where lubricating and corrosion protection is required.

III. Features & Benefits

- **Plastic Safe.** Allows one product to be used in all applications without risk of costly damage to sensitive modern plastics.
- **Inhibits Corrosion.** Increases equipment life and reduces maintenance time.
- **No Class I or Class II Ozone Depleting Chemicals.** Offers effective performance while complying with the EPA regulations on the use of ozone depleting chemicals.
- **M.S.D.[L.]™ Material Safety Data Label** provides instant access to current safety information should an accident or OSHA inspection occur. Helps comply with **OSHA Hazard Communications Standard 29 CFR 1910.1200.**

IV. Physical Properties without propellant

Flash Point	<20° F	Boiling Point	141°F
Odor	Solvent Odor	Solubility	Not soluble in H ₂ O
Appearance	Clear, water-white liquid	% Volatile	97%
Vapor Density	>1 (air = 1)	Specific Gravity	0.6284
VOC Content (Fed)	607 g/L	Propellant	Hydrocarbon
Sara Title III, Sect 313 Chemicals	Yes		
Prop 65	Yes		

V. Specifications and Approvals

- NSF H2 registered (# 017389 aerosol) for use in meat and poultry plants.

VI. Performance Characteristic

Belcore Test (Plastic Compatibility)	Yes
ASTM D-877 (Dielectric Strength)	350 volts
ASTM D-1130 (KB Value)	27

VII. Directions

- Spray light even film on areas to be cleaned and protected.
- Use an extension tube for hard to reach areas.
- Allow to dry thoroughly and vent before reactivating.
- Do not apply while equipment is energized..

VIII. Package Description

Part Number	Container Size
03140	16 oz Aerosol

IX. Disposal

Disposal requirements vary by state and local jurisdiction. All used and unused product should be disposed of in conformance with local, state and federal regulations.

IX. Special Use Warnings

Aerosol Cans

Do not puncture, incinerate or store above 120° F. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

General

Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapor and spray mist. Avoid contact with skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

PRODUCT WARRANTY: CRC offers a conditional warranty on this product for the period of 2 years from the date of manufacture.

DISCLAIMER: This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. All products should be tested for suitability on a particular applications prior to actual use. CRC Industries, Inc. makes no representations or warranties of any kind concerning this data

CRC Industries, Inc.
Technical Service: (800)521-3168

Industrial Products Division
Customer Service: (800)272-4620

Warminster, PA 18974
CRC On-Line: (215)442-6260