Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

BIN#221

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB no. 1218-0072

SAMP 2/3
REC 1/3

IDENTITY (As used on Label and List)
ORTH BURN SPRAY

Note: Blank spaces are not permitted. If any item is not applicable, or no INFORMATION IS AVAILABLE, THE SPACE MUST BE MARKED TO INDICATE THAT

Section I
Manufacturer's Name
CREATIVE PRODUCTS INC. OF ROSSVILLE

Emergency Telephone Number
1800-424-9300

Address (Number, Street, City, State, and ZIP Code)
P.O. BOX 125
ONE CREATIVE WAY
ROSSVILLE, IL 60963

Telephone Number for Information
1-217-748-6784

Date Prepared
JANUARY 16 1998

Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity, Common Names (s))		OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
PROPANE	CAS 75-28-5	1000PPM	NE		
ISOBUTANE	CAS 74-98-6	NE	NE		
BUTANE	CAS 106-97-8	800PPM	800PPM		
DIMETHYL ETHER	CAS 115-10-6	NE			

RECEIVED
SEP - 2 1998

Section III - Physical/Chemical Characteristics

BOILING POINT	NA	SPECIFIC GRAVITY (H2O-1)	.739
VAPOR PRESSURE (mm Hg)	3257	MELTING POINT	NA
VAPOR DENSITY (AIR - 1)	>1	EVAPORATION RATE (BUTYL ACETATE-1)	> 1

SOLUBILITY IN WATER
APPRECIABLE

APPEARANCE AND ODOR
CLEAR SPRAY MENTHOL ODOR FREE

SECTION IV-FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED)	FLAMMABLE LIMITS	LEL	UEL
-100°F ESTIMATED		1.4	18.0

EXTINGUISHING MEDIA
DRY CHEMICAL, FOAM CARBON DIOXIDE

SPECIAL FIRE FIGHTING PROCEDURES
USE WATER SPRAY TO COOL CONTAINERS. AVOID ROCKETING CONTAINERS.

UNUSUAL FIRE AND EXPLOSION HAZARDS
CONTAINERS GENERATE PRESSURE WHEN HEATED CAUSING VIOLENT BURSTING AND DANGEROUS PROPELLING OF CONTAINERS

SECTION V-REACTIVITY DATA

STABILITY	UNSTABLE		CONDITIONS TO AVOID NOT ESTABLISHED
	STABLE	X	

INCOMPATIBILITY (MATERIALS TO AVOID)
OXYGEN AND STRONG OXIDIZING MATERIALS

HAZARDOUS DECOMPOSITION OR BY PRODUCTS
CARBON OXIDES FOAMED WHEN BURNED

HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID NOT ESTABLISHED
	WILL NOT OCCUR	X	

SECTION VI-HEALTH HAZARD DATA

ROUTE(S) OF ENTRY	INHALATION?	SKIN?	INGESTION?
	X	NE	NE

HEALTH HAZARDS(ACUTE AND CHRONIC) HIGH CONCENTRATIONS IN THE AIR CAN CAUSE IRRITATION CAN BE ABSORBED THROUGH THE SKIN.

CARCINOGENICITY: NA NTP? NA IARC MONOGRAPHS? NA OSHA REGULATED? NA

SIGNS AND SYMPTOMS OF EXPOSURE:
DIZZINESS, HEATACHE, ETC.

MEDICAL CONDITIONS:
GENERALLY AGGRAVATE BY EXPOSURE: NONE KNOWN

EMERGENCY AND FIRST AID PROCEDURES:
REMOVE FROM EXPOSURE. WASH THROUGHLY. IF SYMPTOMS CONTINUE SEEK MEDICAL ATTENTION.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
PROTECT FROM IGNITION. ABSORB SPILLED LIQUID WITH COMMERCIAL NON FLAMMABLE ABSORBENT.

WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. CONSULT WITH APPROPRIATE REGULATORY AGENCY PRIOR TO DISPOSAL

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:
STORE BELOW 120°F. IN CASE OF ACCIDENTAL PUNCTURING WITH FORK LIFT SHUT OFF LIFT AND IGNITION SOURCES, VENTILATE AREA.

OTHER PRECAUTIONS
USE ADEQUATE VENTILATION.

SECTION VIII-CONTROL MEASURES

RESPIRATORY PROTECTION(SPECIFY TYPE)
NONE REQUIRED FOR NORMAL HANDLING

VENTILATION	LOCAL EXHAUST FOR SMALL ENCLOSED WORK AREAS.	SPECIAL
	MECHANICAL(GENERAL) ADEQUATE FOR STORAGE	OTHER

PROTECTIVE GLOVES NOT REQUIRED FOR NORMAL HANDLING	EYE PROTECTION NONE REQUIRED FOR NORMAL HANDELING

OTHER PROTECTIVE CLOTHING OR EQUIPMENT
NOT REQUIRED FOR NORMAL HANDLING

WORK/HYGIENIC PRACTICES: NA