

Crimped Wire Wheels with Arbor Hole



Producing an antique finish on a brass door knob rose.

Plater's Wire Wheels - Feature a longer trim length and very small diameter fill material for producing fine satin and antique finishes on non-ferrous and precious metals.



Dia.	Wire Size	Arbor Hole	Face Width	Trim Length	Number of Rows	Max. RPM	Std. Pack	Item Number	
								Brass*	
3"	.003	1/4"	1/2"	1"	2	6,000	12	22021	
4"	.004	1/4"	1"	1-1/4"	4	4,000	5	22061	
6"	.005	1/4"	1"	1-7/8"	4	3,600	1	22241	

* Also available in carbon steel, stainless steel and nickel silver wire.

Small Diameter Crimped Wire Wheels - Identifiable by their copper center, Weiler's small diameter crimped wire wheels feature a plain arbor hole for use on a variety of portable tools and stationary machines. Featuring Weiler's solid ring construction for high-speed use, these radial brushes are available in heat-treated steel, Type 302 stainless steel, and brass wire.

Applications

- Cleaning threads
- Removing rust and light corrosion
- Cleaning and finishing ID's and recessed areas
- Wire stripping
- Light deburring
- Cleaning boiler tubes and internal passages
- Removing carbon build-up and deposits

Small Diameter Wheels - Provide a flexible brushing action and consistent performance for light-duty cleaning and deburring applications requiring a small wheel.



Dia.	Wire Size	Arbor Hole	Face Width	Trim Length	Max. RPM	Standard Pack	Item Number	
							Steel	Stainless
1"	.003	1/4"	3/16"	1/4"	20,000	10	-	16461
	.005						-	16471
	.006						15071	-
1-1/4"	.003	1/4"	1/4"	3/8"	20,000	10	15101	-
	.006						15111	16511
	.008						-	16521
	.008						15732	-
1-3/8"	.006	1/4"	1/4"	3/8"	20,000	10	15131	-
	.008	1/4"					15141	-
	.008	3/8"					15272	-
	.0104	1/4"					15151	-
1-1/2"	.006	3/8"	1/4"	7/16"	20,000	10	15302 ▲	16702
	.008	3/8"		7/16"			15312	16712
	.008	1/2"		1/4"			15753	-
	.0104	3/8"		7/16"			15322	-
	.0118	3/8"		7/16"			15332	-
	.0118	3/8"		7/16"			15332	-
	.014	3/8"		7/16"			15762	-
2"	.003	1/4"	3/8"	3/4"	20,000	10	99307	-
	.003	1/2"					15863	15973
	.005	1/2"					-	16833
	.006	1/2"					15433 ▲	-
	.008	1/2"					15443	16843
	.0104	1/2"					15453	16853
	.0118	1/2"-3/8"					15463 ▲	16863
	.0118	9/16"					15770	-
	.014	1/2"-3/8"					15473	16873
	2-1/2"	.0118					1/2"-3/8"	1/2"
.014		15523	-					
3"	.003	1/2"	5/8"	1"	20,000	10	99551	-
	.006	1/2"		1"			15533	16933
	.006	5/8"		15/16"			15637	-
	.008	1/2"-3/8"		1"			15543	16943
	.008	5/8"		15/16"			15647	-
	.0104	1/2"		1"			15553	-
	.0118	1/2"-3/8"		1"			15563	16963
	.0118	5/8"		15/16"			15667	-
	.014	1/2"-3/8"		1"			15573 ▲	16973
	.014	5/8"		15/16"			15677	17077
	4"	.006		1/2"			1/2"	1-1/2"

▲ Available in non-sparking brass wire, see page 57 for details.

Crimped Wire Wheels with Arbor Hole



22241



15433



15563