

SPECIFICATIONS:

DESCRIPTION

Wall-mounted ADA-compliant sconce featuring handcrafted glass.

MOUNTING

Installs directly to a 4" octagonal outlet box. 75°C supply wire required for incandescent lampping. Top of glass is approximately 3.5" above the outlet box centerline.

LAMPING

Standard lampping shall be 75W max A19. Energy-efficient compact fluorescent options include standard non-dimmable with electronic ballasts or self-ballasted GU-24 types. (Lamps not included)

Consult factory for other configurations (including TBX-type lamps)

CONSTRUCTION

Glass is secured to the backplate by braided wire. Rectangular backplate (nominal 4" W x 6.5" H) shall be constructed of steel, powder-coated white.

DIFFUSER

Diffuser shall be glass, in various decor options.

METAL FINISH

Decorative metal accents shall be in various finish options.

LABELS

UL listed. Suitable for Damp Locations (interior use only).




7041AM-SN

ORDERING:

Fixture/Decor Style	(Lamping Option)	Metal Finish
704107	(blank) Incandescent	BK Black
7041AM	E1 1x 18W Quad 120V	BR Bronze
7041CM	N1 1x 18W Quad 277V	CR Chrome
7041GM	W1 1x 18W GU-24 120V	SN Satin Nickel
7041QM		WH White
7041RM		
7041VM		

7041:

1x 75W A19 or CFL Options



Glass dimensions provided are nominal. Allowance must be made for dimensional tolerance in handcrafted glasses.

REVISED 11/08

Project Information: