location: DAMP interior



SPECIFICATIONS:

DESCRIPTION

Cord-hung or stem-mount pendant with handcrafted glass diffuser. **LED Pendant also available, see website.**

LAMPING

Standard is 75W A19 120V incandescent, suitable for dimming. **CFL:** 26W 4-Pin CFL with non-dimming electronic ballast. 120V. **SB-CFL:** Self-ballasted GU-24 lampholders. 27W max, 120V. Lamps not included.

DIFFUSER

Shade shall be handcrafted glass of various decors. 5.125" Dia. x 10.75" H

SUSPENSION

Cord-hung: 10' SVT-type cord, complete with 5" decorative sleeve at the socketholder. Jacket coordinates with metal finish. Available on 1, 3 or 6 light canopies, shown on next page. Plated stamped steel construction. Bronze or Satin Nickel.

Stem-mount: 4 connectable stem sections (3", 6", 12" and 18" lengths) plus telescoping piece for up to 3" adjustment, 10' max. 5" Dia. canopy (with swivel) and stem sections are plated steel. Bronze or Satin Nickel.

MOUNTING

Installs directly to a 4" octagonal ceiling box. Suitable for sloped ceilings.

LABELS

UL or ETL Listed. Suitable for Damp Locations (interior use only). Consult factory concerning lower wattage labeling for energy requirements.

















1512VM

Vanilla Matte



1512CM

Cobalt Blue Matte



1512TN





For ordering information, see next page

All dimensions provided are nominal.
Allowance must be made for dimensional tolerance in handcrafted glasses.

REV 7/10





ORDERING:


Metal Finish Cord Fixture Decor Lamping 1JC 1 Lt. Dome **151207** Opal Matte () 75W A19 Incand. **BR** Bronze **1JT** 1 Lt. Flat 151280 Amber Matte **H1** 1x 26W TBX SN Satin Nickel 3JB 3 Lt. Linear 1512CH Cherry W* 18W GU-24 max 3JC 3 Lt. Round 1512CM Cobalt Blue Matte H1 avail. on 1JC/1TC only 3JV 3 Lt. Bar 1512HB Habanero *Lamp QTY 3JW 3 Lt. Lrg. Rnd. 1512HV Halva 6JC 6 Lt. Round 1512KR Chalk 1512MA Magma Stem Fixture 15120K Oak 1TC 1 Lt. CFL Dome 1512RM Ruby Matte **1TT** 1 Lt. Flat 1512TN Titan

1512VM Vanilla Matte


PENDANT OPTIONS:

1 Light Canopy


 Dome style (allows install without cutting cord), or Flat style




3 Light Round Canopy



3 Light Linear Canopy



3 Light Large Round Canopy



3 Light Bar Canopy

Some offset installation possible 14.75" 11.25" 4.75" Profile max 11.75" 0 Canopy Underside

CORD SLEEVES:

If concealing the cord is desired, order our 0.25" dia. metal sleeves. Each sleeve is 18" long and may be field cut.

T118-SN Satin Nickel T118-BR Bronze


ADDITIONAL STEM SECTIONS:

Additional connecting stems are available to increase overall length, up to a maximum 10.

7203-SN or T203-BR 3" Section T206-SN or T206-BR 6" Section T212-SN or T212-BR 12" Section T218-SN or T218-BR 18" Section

Project Information:

6 Light Round Canopy



Stem Pendant

- Flat style for incandescent, Dome style for CFL
- Swivel at canopy, suitable for sloped ceilings
- Includes 4 connectable sections (1x 3", 1x 6", 1x 12", 1x 18") plus telescoping piece for up to 3" adjustment

