



Product Name & Number:	Arcadia – WEC25 32219
Collection:	Revival
Construction:	Engineered
Face Species:	Oak (Quercus, spp USA)
Core Species:	Poplar
Number of Plies:	Multi-ply
Thickness:	1/2"
Width:	4"
Grade:	Standard
Profile:	Kissed Edges/Kissed Ends
Face Finish:	Smooth
Finish Treatment:	Aluminum Oxide with ScotchGard Repel
Gloss Level:	30° + or - 5°
Sq. Ft. per Carton:	19.5
Sq. Ft. per Pallet:	780
Cartons per Pallet:	40
Weight per Carton:	35 lbs
Weight per Pallet:	1,400 lbs
Installation:	Uniclic Technology Glue Down/Float On/Above/Below Grade Wood/Concrete Subfloor
Warranties:	25 year Finish 5 year Light Commercial Lifetime Structure Lifetime Moisture
Janka Hardness:	1290
Photo Sensitivity:	1
Character Variation:	Medium

Wood is a natural product and characteristics such as graining, mineral streaking, knots, etc., must be expected. The degree of variation can vary widely within a species and also as a result of environmental conditions prior to harvest.

All wood and laminate flooring should be protected from intense natural and/or artificial UV light exposure to minimize color change.

PRODUCT SPEC SHEET



Janka Wood Hardness Scale is a good indicator of a wood species' resistance to indentations, however all wood will dent and scratch.

7-27-11 Update

Colors	QuarterRound		InstaformProfile		OverlapStairnosing		WoodFiller
Oak Natural-10	HQRTA	05012	HINPA	05012	HSTPE	05012	WF-619
Oak Honey-20	HQRTA	05011	HINPA	05011	HSTPE	05011	WF-635
Oak Cocoa-31	HQRTA	05179	HINPA	05179	HSTPE	05179	WF-651

PRODUCT SPEC SHEET