



①	②	③
52 PCS.	1 PC.	1 PC.

NOTE: Spare crystals enclosed in hardware bag.

IMPORTANT
TURN OFF THE POWER AT THE MAIN FUSE
OR CIRCUIT BREAKER BOX
BEFORE STARTING INSTALLATION

Carefully unpack and identify all parts before assembly. Bulbs are not included.

- 1. Middle Tier Assembly:**
 - A. Spread open middle tier arms so they are evenly spaced to each other.
 - B. Screw threaded pipe into coupler located at bottom section of center body. Then slip notched cap in order to lock arms into position. Fasten with small finial.
- 2. Upper Tier Assembly:**
 - A. Thread fixture wires, located above center body, through center column and fixture loop. Screw center column onto top of center body. Then screw fixture loop onto top of center column.
 - B. Install bottom section of upper tier arm onto threaded stud located at middle tier arm by fastening with ball cap nut. Then install upper section of upper tier arm onto threaded stud located at center column by fastening with ball cap nut. Repeat other arms.
- 3. Lower Tier Assembly:**
 - A. Spread open lower tier arms so they are evenly spaced to each other. Then install the arms onto middle tier arms by fastening with ball cap nuts.
 - B. Install large finial onto bottom section of lower tier arm.
- 4. Follow enclosed "Chain Suspended Fixture Installation Instructions" for electrical and fixture installation onto ceiling outlet box.**
- 5. Hang all crystal glass parts as shown on drawing. NOTE: To replace broken crystals extras are included in hardware bag. Replace by gently bending open pins, remove broken crystal, hook new one, then close back pins. Avoid bending pins into sharp angle.**