



IMPORTANT
TURN OFF THE POWER AT THE MAIN FUSE
OR CIRCUIT BREAKER BOX
BEFORE STARTING INSTALLATION

Carefully unpack and identify all parts before assembly. Bulb is not included.

1. If you are replacing an existing fixture, disconnect and remove the old fixture. Expose the supply wiring from the outlet box.
2. Screw the short threaded pipe 3 complete turns into the flat side of mounting strap and lock in place with hex nut.
3. Fasten the mounting strap to the outlet box using the two screws supplied with the outlet box.
4. Spread the electrical wires so that the black wires are on one side of the outlet box and the white wires are on the other side.
5. Grounding Connection:
 This fixture is provided with a ground wire. Connect fixture ground wire to ground wire from outlet box using wire connector (not provided).
 Never connect ground wire to black or white power supply wires.
6. Electrical wire connection:
 Connect the white wire(s) from the fixture to the white wire of the outlet box. Connect the black wire(s) from the fixture to the black wire of the outlet box.
 NOTE: Black outlet box wire may be red, round & smooth and/or have copper conductor. White outlet box wire may be square & ridged and/ or have a silver conductor.
7. Place crown through short threaded pipe so that crown sits flush against ceiling. Be sure all wires are inside crown. Secure crown to ceiling by screwing with coupler, which is located at top end of center pipe, onto protruding threaded pipe. Coupler must turn at least 3 times, if it does not then must lengthen threaded pipe accordingly.
8. Install bulbs (not included). See relamping label located located at socket area for type and maximum allowed wattage.
9. Gently sit glass shade inside of main frame. Then slide the main frame up until it checks inside of crown. Lock them into position by fastening with finial.