

**IMPORTANT
TURN OFF THE POWER AT THE MAIN FUSE
OR CIRCUIT BREAKER BOX
BEFORE STARTING INSTALLATION**

Carefully unpack and identify all parts before assembly. Bulb is not included.

1. Screw short threaded end of center pipe into top coupler.
2. Slip middle cover, break and top cover through the installed center pipe. Lock all together by fastening with finial.
3. Lift up door latch and open door.
4. Place candle tubes over candleabra sockets and screw bulbs (not included) into sockets to secure. See relamping label on candle tube for type and maximum allowed wattage.
5. Close door shut and lock by pushing door latch down so it locks into small cylinder below.
6. Electrical installation onto post: If you are replacing an existing fixture, disconnect and remove the old fixture.


A) Slip post cup over post. Mark position of holes in post cup over post on post.

B) Remove post cup and expose the supply wiring from above post. Drill 1/8" (3mm) diameter pilot holes in post at places where marked.

C) Make wire connections. (wire connectors not provided). Refer to chart below for correct connections. Wire supply wires to fixture wires accordingly.

Connect Black Fixture Wire to:	Connect White Fixture Wire to:
Black Supply Wire or *Parallel cord (round & smooth)	White Supply Wire or *Parallel cord (square & ridged)
Clear, Brown, Gold or Black without tracer Insulated wire (other than green) with copper conductor	Clear, Brown, Gold or Black with tracer Insulated wire (other than green) with silver conductor

*Note: When parallel wire (SPT 1 & SPT2) is used. One wire is square shaped or ridged and the other wire will be round in shape or smooth. (See Illustration)



D) Connect ground wire from supply source to fixture ground wire with connector. Never connect ground wire to black or white power supply wires. Carefully place wires inside post.

E) Slip post cup onto post. Align holes in post cup with holes in post. Attach post cup to post with sheet metal screws