

ASSEMBLY AND INSTALLATION

INSTRUCTIONS

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF **POWER BEFORE** INSTALLING OR SERVICING THIS FIXTURE.

Installation Steps

- Carefully unpack your new fixture and lay out all the parts on a clear surface.
- Thread Hex nut-2 onto the Nipple-1, place the Washer over the end of Nipple-1, thread Nipple-1 through Mounting bar and secure with Hex nut-1 continue until tight.
- Thread the Ground screw into the hole near the two dimples of the Mounting bar. Secure the Mounting bar to the outlet box with the Outlet box screws.
- Place the four Glasses into each side of the Cage. (Remark: One side of the sandblast **Glass faces outward**). Thread the Short nipple into the Ball nut, place the Steel washer, and then thread it to through the hole of the Cage. (Remark: Steel washers keep the **Glass and Cage tight**.)
- Install the light bulbs in accordance with the fixture's specifications. **DO NOT EXCEED THE MAXIMUM WATTAGE RATING!**
- Secure the fixture Arms to Cage with Screws.
- Thread the Nipple-2 into the Coupling-1.
- Thread the Nipple-3 into the Coupling-2, then thread the Hex nut-3 onto the Nipple-3, slide the Cap onto the Nipple-3 and secure with the Finial. (Remark: Hex nut-3 keep the Coupling-2 and Cap are horizontal.)
- Weave the Fixture Wire and the Ground Wire through the Chain links. Open Key link-2, connect Loop to one end link of the Chain and close the Key link-2.
- Thread the Fixture Wire and ground wire through the Collar ring, Canopy, Nipple-1 and Mounting bar in order.
- Secure the Collar ring to the Nipple-1, Open Key link-1, connect Collar ring to the other one link of Chain and close the Key link-1.
- Make Wire connections with Wire Connector:
 - The smooth wire (w/ marking) from fixture to Black Wire from power source.
 - The ribbed wire (w/o marking) from Fixture to White Wire from power source.
 - Attach the Ground Wire and house ground wire to the Mounting bar with **the** green Ground Screw. Carefully tuck wires back into the Outlet Box.
- Attach the Canopy to the Mounting bar by inserting the Collar ring, and then secure with the collar ring.
- Turn on the power at fuse or Circuit Box.

