

Bona® Pro Series Stone, Tile & Laminate Floor Refresher

Technical data sheet

Professional formula refresher provides a clear, highly durable gloss to all sealed hard surface flooring including: laminate flooring, vinyl, no-wax linoleum, terrazzo, unglazed tile (ceramic, Mexical Saltillo, quarry), stone, and sealed porous marble. Waterborne acrylic formula fortified with urethane.

- Professional Formula
- Keeps floors looking new
- Quick and easy application
- Dries in one hour
- Waterborne acrylic formula with urethane
- Non-toxic
- GREENGUARD certified for indoor air quality

Technical data

Physical Characteristics:

Ingredients – Water, acrylic polymer, urethane, wax, Diethylene Glycol Monoethyl Ether

Color – Milky white (wet)

pH –8.0

Solids – 10% - 12%

Viscosity – (#4 Ford cup @ 25° C) 10-12 seconds

Density – 8.39 lbs./gallon (1.01 S.G.)

Packaging – 1 quart plastic bottle

Gloss Level – (60°)>85

Odor – Non-Offending

Flash Point – Non-flammable

Stability – 1 year shelf life

VOC – Does not exceed 2%

Application Characteristics:

Drying Time – 1 hour

Application Tools – Bona® Microfiber Applicator Pad

Coverage – 500 sq. ft. per bottle

Clarity – Clear when dry

Leveling – Excellent

Percent Cured After 24 hours – 90%

Defoaming – Excellent

Max. Cure – 100% after 1 week

Recommended Use

- Use every 2-3 months on all sealed hard surface flooring

Directions

BEFORE USING, READ ALL DIRECTIONS AND MATERIAL SAFETY DATA SHEET.

1. Remove furniture, rugs, etc. Vacuum, sweep or dust mop, then thoroughly clean with Bona Stone, Tile & Laminate Floor Cleaner and the green Microfiber Cleaning Pad on your Bona Mop. Allow the floor to dry. 2. Gently rock product back and forth to mix. Slightly dampen the cream Microfiber Applicator Pad with water and attach to mop. Squirt Stone, Tile & Laminate Floor Refresher onto the floor and spread. Work in sections small enough to keep the Applicator Pad wet. Continue working in sections until the entire floor is finished. Rinse Applicator Pad with water. 3. Allow to dry at least 1 hour before walking on the floor. For a glossier floor, a second coat may be applied after 2 hours. Allow 24 hours before heavy traffic.

For best results: Always test in an inconspicuous section of the floor before use. Coverage should be 500 square feet per bottle. Do not apply the product too thin or streaking will occur. Coat the entire floor to ensure an even appearance.

1. Clean
2. Squirt and Spread
3. Allow to Dry

Maintenance

Clean-Up: Clean all tools and equipment with warm water.

Finishing



Bona®