















Notice: Please review the parts listing and check for all parts before assembling the fixture. If any parts are missing or damaged, please note on this sheet and contact the place of purchase to arrange for replacement parts.

PARTS LIST

Company Name: _____ Co. Account #: _____
to be filled out by retailer

Canopy  1ea $\varnothing 1-1/2'' \times H5\text{mm}$	Nipple  1ea $1/8\text{-IP} \times H45\text{mm}$	ROD  1ea $1/8\text{-IP} \times H122\text{mm}$
Finial  1ea $\varnothing 1-1/4'' \times H49\text{mm}$	Wire connectors  3ea P3 Orange	Mounting Screws  2ea $8\#32\text{-IP} \times 1-1/2''$
Mounting Strap  1ea $\varnothing 4'' \times H10\text{mm}$	Mounting Screws  2ea $8\#32\text{-IP} \times 1''$	Hex Nut  2ea $5/32\text{-IP} \times H3\text{mm}$
Wire connectors  3ea P3 Orange	Nipple  1ea $\varnothing 1'' \times H3\text{mm}$	Flat washer  1ea $\varnothing 1-1/2'' \times H2\text{mm}$
Hex Nut  1ea $1/8\text{-IP} \times H4\text{mm}$	Rubber Washer  1ea $\varnothing 1-1/2'' \times H2\text{mm}$	

Part Needed _____	Quantity _____
Part Needed _____	Quantity _____
Reason why (missing, scratched, broken glass, bent, bad finish)	
Comments _____	

FIXTURE ASSEMBLY INSTRUCTIONS


Read and review installation instruction sheet before assembling the fixture.

1. Thread the Nipple (K) into the fixture pan coupling (J).
2. Install the light bulbs in accordance with the fixture's specifications.
3. Thread Nipple (S) into Rod (K). Slide Flat Washer (R) and Glass (L) onto Nipple (S). Then put Cap (T), Rubber Washer (M), and Flat washer (N) onto Nipple (S).
4. Thread Hex Nut (O) onto Nipple (S) to secure.
5. Slide Canopy (P) onto Nipple (S). Secure with Finial (Q).

DO NOT EXCEED MAXIMUM WATTAGE RATING!

NOTE: INSTALL THE GLASS ASSEMBLY AFTER THE FIXTURE IS HUNG.

8118-FM PW



WARNING ! SHUT OFF POWER AT FUSE OR CIRCUIT BREAKER.

HANGING THE FIXTURE (Fig.1)

1. Carefully remove the new fixture from the carton and the yellow bag that holds all your parts. Check that all parts are included as shown in the illustration and parts list.
2. Shut off power at the circuit breaker and remove the old fixture from ceiling, including the old mounting strap.
3. Thread the two Fixture Mounting Screws (G) into the pre-drilled Holes in the Mounting Strap (E) spaced the same distance apart as the holes in the ceiling pan. Secure in place with Hex nuts (F).
4. Attach Mounting Strap (E) to the junction box using the two Mounting Screws (D)

CONNECTING THE WIRES (Fig 2)

5. Attach the power supply wires to the fixture lead wires by connecting BLACK to BLACK (or SMOOTH) and WHITE to WHITE (or RIBBED).
6. Attach the GROUND wire (GREEN or COPPER) from the Junction Box and the fixture Ground wire to the green Ground Screw (L) on the Mounting Bracket (E) or connect both wires together using a wire connector. NOTE: Twist the wires together in the same direction you twist the wire connector onto the wires.
7. Tuck these wire connections neatly into the Junction Box.

FINISHING THE INSTALLATION

8. Finish mounting the Ceiling Pan (J) by placing it over the Mounting Strap (E) as shown in Fig. 1. Rotate the pan until the Mounting Screws (G) protrude through the "Keyholes" located in the bottom of Ceiling Pan (J). Using a screwdriver, secure the Ceiling Pan (D) by screwing Mounting Screws (G) until tight.
9. Install the light bulbs in accordance to the fixture's specifications.
10. Install the glass shade according to the assembly instructions.

Fig. 1




Fig. 2





Fig. 3



YOUR INSTALLATION IS NOW COMPLETE. RETURN POWER TO THE JUNCTION BOX AND TEST THE FIXTURE.