

1. Attach mounting strip to outlet box using outlet box screw (shorter).
2. Secure support screws into mounting strip. Do not tighten.
3. Thread stem B to connect, Thread stem A into stem B until tight. repeat for any additional stem .
4. Connect the wires from the fixture to the power supply wires outlet box.
 - A. Twist together white wire from the fixture with wire from post. Cover with wire connector.
 - B. Twist together black wire from the fixture with black wire from post. Cover with wire connector.
 - C. Wrap the bare ground wire from the fixture and the outlet box around the green ground screw located on the mounting strip. Tighten the green ground screw to the mounting strip.
4. Pass canopy through the support screws of mounting strip. Tighten cap nut onto the protruding support screws on mounting strip until the fixture body is held firmly to the ceiling.
5. Install the bulb (not included) into socket. Do not use greater than 60-watt bulb.
6. Thread nipple to bushing and secure with nut.
7. Place glass over nipple, and secure by tightening with washer and finial.

NOTE: Carefully remove the fixture from the carton. Check that all parts shown in package parts 1 and parts 2 are included. Be carefully not to misplace any of the screws or wire connectors, which are needed for installing the fixture.

PACKAGE PART

Wire connector	2	Glass	1
Green ground screw	1	Nut	1
Outlet box screws	2	Nipple	1
Support screw	2	Washer	1
Mounting strip	1	Finial	1
		Cap nut	2

