



ASSEMBLY INSTRUCTION

ITEM# 33271

1. Tighten support screw (longer) 2 full turns into mounting strip. Secure with 5/32" hex nut (to be fully tightened later).
The support screw should extend long enough to protrude the canopy when it is mounted.
2. Fasten mounting strip onto outlet box using outlet box screw (shorter).
3. Connect the wires from the fixture to the power supply wires from outlet box. Cover with wire connectors.
 - a) Twist together white wire from the fixture with white wire from outlet box. Cover with connectors.
 - b) Twist together black wire from the fixture with black wire from outlet box. Cover with connectors.
 - c) Wrap the ground wires from the fixture and outlet box around the green ground screw located on the mounting strip.
Tighten the green ground screw to the mounting strip.
4. Place canopy over outlet box. Let heads of support screw (longer) come through the holes of the canopy, then secure by tightening with ball nut.
5. Thread nipple into bushing. Secure with hex nut.
6. Install the bulbs (not included). Do not use greater than 60-watt the bulbs.
7. Thread nut, washer, rubber, washer and secure with hex nut. Slide glass, washer and secure with hex nut (Do not too tighten), Then set cap and secure by tightening with finial.

NOTE: Carefully remove the fixture from the carton. Check that all parts shown in package parts 1 and parts 2 are included. Be carefully not to misplace any of the screws or wire connectors, which are needed for installing the fixture.

Package parts

Wire connector	2	NIPPLE	1
Green ground screw	1	NUT	4
Outlet box screw	2	WASHER	1
Mounting strip	1	RUBBER	1
Support screw	2	CAP	1
5/32"Nut	2	FINIAL	1

