WALL MOUNT INSTALLATION INSTRUCTIONS

READ AND SAVE THESE INSTRUCTIONS

CAUTION: BEFORE ASSEMBLING YOUR LIGHTING FIXTURE, REFER TO THE SECTION TITLED ELECTRICAL CONNECTIONS. IF YOU FEEL THAT YOU DO NOT HAVE ELECTRICAL WIRING EXPERIENCE, REFER TO A YOURSELF WIRING HANDBOOK OR HAVE YOUR FIXTURE INSTALLED BY A QUALIFIED LICENSED ELECTRICIAN.

ASSEMBLE THE FIXTURE (NOTE: FIRST TURN OFF ELECTRICITY)

REFER TO FIGURES FOR ILLUSTRATION OF TYPICAL FIXTURE PARTS AND ASSEMBLIES.

- 1. IF YOU ARE REPLACING AN EXISTING FIXTURE, DISCONNECT AND REMOVE THE OLD FIXTURE. EXPOSE THE WIRING IN THE OUTLET BOX.
- 2. ATTACH CROSS BAR TO THE OUTLET BOX WITH THE (2) SCREW.
- 3. CONNECT THE WHITE FIXTURE WIRE TO THE WHITE SUPPLY WIRE USING A WIRE CONNECTOR. CONNECT THE BLACK FIXTURE WIRE TO THE BLACK SUPPLY WIRE IN THE SAME MANNER. CONNECT THE SUPPLY GROUND WIRE ONTO THE CROSS BAR USING THE GREEN SCREW..
- 4. RAISE THE FIXTURE OVER THE CROSS BAR. INSERT THE SUPPLIED THUMB NUTS INTO THE DESIGNATED HOLES ON THE SIDES OF THE FIXTURE BACK PLATE AND SECURE IT.
- 5. INSTALL THE LIGHT BULB, RESTORE THE ELECTRICITY AND ENJOY YOUR NEW FIXTURE.

