



WALL MOUNT INSTALLATION INSTRUCTIONS

READ AND SAVE THESE INSTRUCTIONS

39410/1 & 39410/2

CAUTION: BEFORE ASSEMBLING YOUR LIGHTING FIXTURE, REFER TO THE SECTION TITLED ELECTRICAL CONNECTIONS. IF YOU FEEL THAT YOU DO NOT HAVE ELECTRICAL WIRING EXPERIENCE, REFER TO A YOURSELF WIRING HANDBOOK OR HAVE YOUR FIXTURE INSTALLED BY A QUALIFIED LICENSED ELECTRICIAN.

ASSEMBLE THE FIXTURE (NOTE: FIRST TURN OFF ELECTRICITY)

REFER TO FIGURES FOR ILLUSTRATION OF TYPICAL FIXTURE PARTS AND ASSEMBLIES.

1. IF YOU ARE REPLACING AN EXISTING FIXTURE, DISCONNECT AND REMOVE THE OLD FIXTURE. EXPOSE THE WIRING IN THE OUTLET BOX.
2. ATTACH CROSS BAR TO THE OUTLET BOX WITH THE (2) SCREW.
3. CONNECT THE WHITE FIXTURE WIRE TO THE WHITE SUPPLY WIRE USING A WIRE CONNECTOR. CONNECT THE BLACK FIXTURE WIRE TO THE BLACK SUPPLY WIRE IN THE SAME MANNER. CONNECT THE SUPPLY GROUND WIRE ONTO THE CROSS BAR USING THE GREEN SCREW.
4. FIT THE FIXTURE BACK PLATE OVER THE CROSSBAR, SUCH THAT THE NIPPLE FITS THROUGH THE DESIGNATED HOLE IN THE FIXTURE BACK PLATE. SECURE THE FIXTURE BACK PLATE WITH THE SUPPLIED THUMB NUT BY SCREWING IT ONTO THE END OF THE NIPPLE. THE THUMB NUT OR BALL NUT(FOR THE 2LIGHTS WALL MOUNT) SHOULD SIT FLUSH TO THE FIXTURE BACK PLATE (SO YOU MAY NEED TO ADJUST THE NIPPLE LENGTH).
5. INSTALL GLASS SHADE, SOCKET RING AND THE LIGHT BULB ACCORDINGLY.
6. RESTORE ELECTRICITY AND CHECK THE OPERATION OF YOUR NEW LIGHTING FIXTURE.

