

# U Series/U317/UTR1 Rackshelves

**EIA/TIA Compliant** 

middleatlantic.com

## U Series / U317 / UTR1 Rackshelves

## **Features**

U Series - Universal rackshelves

- Available in 1 through 4 rackspaces
- Weight capacity from 35 to 85 lbs. depending on size
- Accommodates most standard non-rackmountable components
- · See chart for part numbers and dimensions
- Contractor packs available
- UL Listed in the US and Canada

U317 - Vented 3 space rackshelf

- 17-3/4" depth allows for deeper components
- 60 lb. weight capacity
- Vent pattern provides superior air circulation
- · Slotted rear flange for cable management

UTR1 - Half / third rack shelf

- 25 lb. weight capacity
- Universal mounting hole pattern accommodates virtually any half or third space component
- · Equipment mounting hardware included
- Contractor packs available



U2



**U317** 



## **Architects' and Engineers' Specifications**

#### U Series

Solid, one-piece 16-gauge steel rackshelf shall be Middle Atlantic Products model # Ux (x = # of rackspaces, refer to chart). Weight capacity shall be \_\_(refer to chart). Rackshelf shall feature durable flat black powder coat finish. Contractor packs shall be available with twelve U1 or six U2 rackshelves and shall be model # U1-RP12 or U2-RP6. U series rackshelf shall be warrantied to be free from defects in material or workmanship under normal use and conditions for the lifetime of the product. U series rackshelf shall be UL Listed in the US and Canada.

### U317

Vented three rackspace rackshelf shall be Middle Atlantic Products model # U317. One-piece, 16-gauge rackshelf shall provide a 60 lb. weight capacity. U317 shall features slotted rear flange for cable management. Depth of 17-3/4" shall accomodate deeper components. U317 shall be warrantied to be free from defects in material or workmanship under normal use and conditions for the lifetime of the product.

### UTR1

Half / third rack shelf with 10" depth shall be Middle Atlantic Products model # UTR1. UTR1 shall feature universal mounting hole pattern to accomodate virtually any half or third space component. UTR1 shall include four 6-32x1/4 screws, four 8-32x1/4 screws and two 10-32x1/4 screws for component mounting. Contractor packs shall be available with twelve UTR1 rackshelves and shall be model # UTR1-RP12. UTR1 shall be warrantied to be free from defects in material or workmanship under normal use and conditions for the lifetime of the product.

electronic version available at middleatlantic.com

#### U Series / U317 / UTR1 basic dimensions All dimensions in inches unless otherwise noted [Bracketed dimensions in millimeters] **U** Series 17.56 [446] .56 [14] (rear flange) **TOP** SIDE **VIEW VIEW** В Ċ **RACKING** HEIGHT / OVERALL USEABLE **RACKSPACES** DEPTH DEPTH WEIGHT PART # "B" "C" "D" CAPACITY "A" 17.38 [441] U1 1.75 [44] (1 SP) 10.75 [273] 10.69 [272] 6.05 [154] 35 lbs. [16 kg] 3.50 [89] (2 SP) 50 lbs. [23 kg] 14.56 [370] 14.38 [365] 6.49 [165] U2 .31 [8] front flange **FRONT VIEW** U3 5.25 [133] (3 SP) 14.56 [370] 14.38 [365] 5.71 [145] 70 lbs. [32 kg] on U2, U3 and U4 U4 7.00 [178] (4 SP) 15.50 [394] 15.31 [389] 6.00 [152] 85 lbs. [39 kg] only **U317** .63 [16] .31 [8] (rear flange depth) (rear flange) 17.75 17.86 [451] SIDE [454] **TOP** useable **VIEW VIEW** overall depth depth 5.00 [127] 5.25 [133] 17.38 [441] 5.25 **FRONT VIEW** [133] .31 [8] (front flange) UTR1 17.38 [441] <u>TOP</u> 10.00 **VIEW** [254]

