

# INSTALLATION INSTRUCTIONS FOR 8841-64

## For Wall Mount Fixture

**WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER .**

### MOUNTING THE FIXTURE

- |  |   |
|--|---|
| <p><b>Installation (see fig.1)</b></p> <ol style="list-style-type: none"> <li>1. Shut off the power at the circuit breaker and remove old fixture, including the crossbar.</li> <li>2. Thread the nipple part way into the center hole of the crossbar and secure with hex nut.</li> <li>3. Attach the crossbar to the junction box using two junction box screws. The side of the crossbar marked "GND" must face out.</li> <li>4. Follow wiring instructions carefully (see fig.2)</li> <li>5. Place the glass shade (C) into the frame (F).</li> <li>6. Place the nipple with hex nut (A) into the washer (B) and insert into hole inside of backplate. Thread the nipple (A) into nut (D), aligning hole of the rubber washer (E), glass shade (C) and the frame (F) with nipple threads and then screw it with the finial (H).</li> <li>7. Place the fixture body (F) over the nipple, then tighten it with the cap nut (G).</li> <li>8. Install the light bulbs in accordance with the fixture's <b>specifications. DO NOT EXCEED THE MAXIMUM WATTAGE RATING!</b></li> </ol> | <p><b>Wiring (see fig.2)</b></p> <ol style="list-style-type: none"> <li>1. Connect the electrical wires as follows. Connect the black wire from the fixture to the black house (hot) Wire. Connect the white wire from the fixture to the white (neutral) house wire. Make sure all wire nuts are secured. You may wrap the connections with electrical tape. If your outlet box has a ground wire (green or bare copper) connect fixture's ground wire to it. Otherwise attach the bare copper fixture wire to the green ground screw on the crossbar.</li> <li>2. Tuck the wire connections neatly into the wall junction box.</li> </ol> |
|--|---|

