## INSTALLATION INSTRUCTION FOR 8800-65 For Mini Pendant Mount Fixtures

## WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

## ASSEMBLING THE FIXTURE (Fig.2)

- 1. Attach the loop (A) to the fixture body (B) by turning it clockwise until tight.
- 2. Place the shade (D) onto the socket of the fixture body (B) then secure it in, place with socket ring (E) and screw shell (F) securely tighten.
- 3. Attach the crystal (C) to the small ring of the fixture body (B).

## **HANGING THE FIXTURE (Fig.1)**

- 1. Shut off the power at the circuit breaker and remove old fixture from ceiling, including the old crossbar.
- Carefully unpack new fixture and lay all the parts on a clear surface.
- 3. Thread the two Studs (A) about 1/4"into the pre-drilled holes in the mounting strap spaced the same distance apart as the holes in the fixture canopy (B).
- 4. Install the mounting strap to the Junction Box with the two Junction Box Screws as shown. The side of the mounting strap marked "GND" must face out.
- 5. While holding the canopy and lamp cluster towards the ceiling, connect the electrical wires as Shown in Fig.3, making sure that all wire connectors are secured. You may have to wrap the connections with electrical tape. If there is a Ground Wire (green or bare copper) in your outlet box, connect the fixture's Ground Wire to it. Otherwise connect fixture's ground wire directly to the mounting strap with the Green Screw provided. After wires being connected, tuck them carefully inside the Junction Box.
- 6. Then cover the junction box with canopy (B), aligning the Screw of mounting plate with the hole of canopy and lock it with brass ball (C).
- 7. Open one the end link of the chain provided and connect to the fixture loop (E). Close the link.
- 8. Lace the fixture wires through the chain.
- 9. Open the other end link of the chain and hang the fixture on the loop at the ceiling. Close the link.
- 10. Lace the fixtue wires, ground wires through the loop and canopy (B) and pull until taut.
- 11. Attach the crystal (D) to the small ring of the fixture body (B).
- 12. Install the light bulbs in accordance with the fixtur specifications **NOTE: DO NOT EXCEED THE SPECIFIED WATTAGE.**

Your installation is now complete Return power to the junction box and test the fixture.







