YHD item number	рното	Item type/ product type (ext light, portable lamp, wall sconce, bulb, ceiling fan)	water pump model	pump image	pump specification	light	LED Light Image	LED Light Specification
CW08002		Fountain	P-WP1500		6.7' Max Lift, Max Flow Rate is 2000 L/H, 12' Cord, 6.57" L x 2.95" W x 4.09" H, 45 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SINGLE-LED		
CW08013	La constante da constante constante da constante da constante constante da constante constante da constante	Fountain	PPP-PP399		5.9' Max Lift, Max Flow Rate is 1000 L/H, 12' Cord, 3.46" L x 2.83" W x 3.18" H, 16 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SINGLE-LED		
CW08044		Fountain	PPP-PP388	Johnson Ministrati	4.3' Max Lift, Max Flow Rate is 600 L/H, 12' Cord, 2.71" L x 2" W x 2.48" H, 12 Watts, 110V/60Hz AC UL approved	1 P-QFOUN-SIX-LED		
CW08048		Fountain	P-WP350-SF	ALL OF	max flow rate:1200gph; 120v 60hz; 99 watts; 5"L x 3.75"W x 5" H; tube connector 1/2", 3/4" and 1" (diameter); head max 13.5ft	3 P-QFOUN-SIX-LED		

CW08055		Fountain	P-WP450		3.7' Max Lift, Max Flow Rate is 450 L/H, 12' Cord, 2.4" L x 1.69" W x 1.77" H, 5 Watts, 110V/60Hz AC UL approved	BANK LIGHT	
CW08060-4		Fountain	P-WP350-SF	John States	2.7' Max Lift, Max Flow Rate is 350 L/H, 12' Cord, 2.24" L x 1.61" W x 1.81" H, 6 Watts, 110V/60Hz AC UL approved		
CW08061	P	Fountain	P-WP350-SF	John Chu	2.7' Max Lift, Max Flow Rate is 350 L/H, 12' Cord, 2.24" L x 1.61" W x 1.81" H, 6 Watts, 110V/60Hz AC UL approved		
CW08064		Fountain	P-WP450		3.7' Max Lift, Max Flow Rate is 450 L/H, 12' Cord, 2.4" L x 1.69" W x 1.77" H, 5 Watts, 110V/60Hz AC UL approved	BANK LIGHT 1 P-QFOUN- SIX-LED	

CW08146		Fountain	P-WP650	Active States	5.5' Max Lift, Max Flow Rate is 700 L/H, 12' Cord, 2.79" L x 2" W x 2.24" H, 10 Watts, 110V/60Hz AC UL approved	P-QFOUN-333-4COLOR-LED	
CW09003	NAN	Fountain	PPP-PP399		5.9' Max Lift, Max Flow Rate is 1000 L/H, 12' Cord, 3.46" L x 2.83" W x 3.18" H, 16 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SINGLE-LED	
CW09005	ALL	Fountain	PPP-PP399		5.9' Max Lift, Max Flow Rate is 1000 L/H, 12' Cord, 3.46" L x 2.83" W x 3.18" H, 16 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SINGLE-LED	
CW09019		Fountain	P-WP2000		11.8' Max Lift, Max Flow Rate is 2000 L/H, 12' Cord, 4.17" L x 2.95" W x 4.01" H, 45 Watts, 110V/60Hz AC UL approved	4 P-QFOUN-SINGLE-LED	

CW09022	物	Fountain	P-WP350-SF	John Com	2.7' Max Lift, Max Flow Rate is 350 L/H, 12' Cord, 2.24" L x 1.61" W x 1.81" H, 6 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SINGLE-LED	
CW09031		Fountain	P-WP5000N		19.6' Max Lift, Max Flow Rate is 5000 L/H, 12' Cord, 8.18" L x 4.29" W x 5.12" H, 190 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SIX-LED	
CW09040		Fountain	P-WP2000		11.8' Max Lift, Max Flow Rate is 2000 L/H, 12' Cord, 4.17" L x 2.95" W x 4.01" H, 45 Watts, 110V/60Hz AC UL approved	2 P-QFOUN-SIX-LED	
CW09052		Fountain	P-WP2350		13.8' Max Lift, Max Flow Rate is 2350 L/H, 12' Cord, 4.17" L x 2.95" W x 4.09" H, 60 Watts, 110V/60Hz AC UL approved	2 P-QFOUN-SIX-LED	

CW09058	Fountain	P-WP450	and the second s	3.7' Max Lift, Max Flow Rate is 450 L/H, 12' Cord, 2.4" L x 1.69" W x 1.77" H, 5 Watts, 110V/60Hz AC UL approved	2 P-QFOUN-SIX-LED	
CW09062	Fountain	P-WP650	A second	5.5' Max Lift, Max Flow Rate is 700 L/H, 12' Cord, 2.79" L x 2" W x 2.24" H, 10 Watts, 110V/60Hz AC UL approved	1 P-QFOUN-SIX-LED	
CW09063	Fountain	P-PP399		5.9' Max Lift, Max Flow Rate is 1000 L/H, 12' Cord, 3.46" L x 2.83" W x 3.18" H, 16 Watts, 110V/60Hz AC UL approved	1 P-QFOUN-SIX-LED	
CW09071	Fountain	P-PP333LV	A Constant of the second secon	2.5' Max Lift, Max Flow Rate is 250 L/H, 12' Cord, 1.89" L x 1.73" W x 1.14" H, 2.5 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SINGLE-LED	

CW09072	Fountain	P-WP650	A DECEMBER OF A	5.5' Max Lift, Max Flow Rate is 700 L/H, 12' Cord, 2.79" L x 2" W x 2.24" H, 10 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SINGLE-LED	
CW09076	Fountain	P-WP450		3.7' Max Lift, Max Flow Rate is 450 L/H, 12' Cord, 2.4" L x 1.69" W x 1.77" H, 5 Watts, 110V/60Hz AC UL approved	1 P-QFOUN-SIX-LED	
CW09140	Fountain	P-PP333LV	A Contract of the Contract of	2.5' Max Lift, Max Flow Rate is 250 L/H, 12' Cord, 1.89" L x 1.73" W x 1.14" H, 2.5 Watts, 110V/60Hz AC UL approved	P-QFOUN-333-4COLOR-LED	
CW09156	Fountain	P-WP350-SF	A DE LE DE L	2.7' Max Lift, Max Flow Rate is 350 L/H, 12' Cord, 2.24" L x 1.61" W x 1.81" H, 6 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SINGLE-LED	

CW09162	Fountain	P-HKP-HK200LV	Enternal Property and a constrained of the constrai	1.96' Max Lift, Max Flow Rate is 150 L/H, 12' Cord, 1.45" L x 1.1" W x 1.42" H, 2.5 Watts, 110V/60Hz AC UL approved	1 P-QFOUN-SIX-LED	
CW09163	Fountain	P-HKP-HK200LV	Submersible Pump	1.96' Max Lift, Max Flow Rate is 150 L/H, 12' Cord, 1.45" L x 1.1" W x 1.42" H, 2.5 Watts, 110V/60Hz AC UL approved	1 P-QFOUN-SIX-LED	
CW10006	Fountain	P-WP2000		11.8' Max Lift, Max Flow Rate is 2000 L/H, 12' Cord, 4.17" L x 2.95" W x 4.01" H, 45 Watts, 110V/60Hz AC UL approved	4 P-QFOUN-SINGLE-LED	
CW10016	Fountain	P-WP2000		11.8' Max Lift, Max Flow Rate is 2000 L/H, 12' Cord, 4.17" L x 2.95" W x 4.01" H, 45 Watts, 110V/60Hz AC UL approved	1 P-QFOUN-SIX-LED	

CW10020		Fountain	P-SP3000T		13.78' Max Lift, Max Flow Rate is P-SP3000TL/H, 12' Cord, 4.96" L x 3.74" W x 4.72" H, 70 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SIX-LED	
CW72011	88433	Fountain	P-WP450		3.7' Max Lift, Max Flow Rate is 450 L/H, 12' Cord, 2.4" L x 1.69" W x 1.77" H, 5 Watts, 110V/60Hz AC UL approved	1 P-QFOUN-SIX-LED	
CW72016		Fountain	P-WP5000N		19.6' Max Lift, Max Flow Rate is 5000 L/H, 12' Cord, 8.18" L x 4.29" W x 5.12" H, 190 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SIX-LED	
CW73024		Fountain	P-WP1500	······································	6.7' Max Lift, Max Flow Rate is 2000 L/H, 12' Cord, 6.57" L x 2.95" W x 4.09" H, 45 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SIX-LED	

CW84062	U	Fountain	P-PP333LV	Part Part Part Part Part Part Part Part	2.5' Max Lift, Max Flow Rate is 250 L/H, 12' Cord, 1.89" L x 1.73" W x 1.14" H, 2.5 Watts, 110V/60Hz AC UL approved	4 COLOR LED	
CW85020		Fountain	P-WP750		5.51' Max Lift, Max Flow Rate is 700 L/H, 12' Cord, 2.79" L x 2" W x 2.24" H, 10 Watts, 110V/60Hz AC UL approved	1 P-QFOUN-SIX-LED	
CW85022		Fountain	P-WP350-SF	John Caller	2.7' Max Lift, Max Flow Rate is 350 L/H, 12' Cord, 2.24" L x 1.61" W x 1.81" H, 6 Watts, 110V/60Hz AC UL approved	1 P-QFOUN-SIX-LED	
CW85079	*	Fountain	P-PP333LV	A second	2.5' Max Lift, Max Flow Rate is 250 L/H, 12' Cord, 1.89" L x 1.73" W x 1.14" H, 2.5 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SINGLE-LED	

CW85083	Fountain	P-WP350-SF	2.7' Max Lift, Max Flow Rate is 350 L/H, 12' Cord, 2.24" L x 1.61" W x 1.81" H, 6 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SINGLE-LED	
CW96005	Fountain	P-WP1500	6.7' Max Lift, Max Flow Rate is 2000 L/H, 12' Cord, 6.57" L x 2.95" W x 4.09" H, 45 Watts, 110V/60Hz AC UL approved	1 P-QFOUN-SIX-LED	
CW96019	Fountain	P-PP388	4.3' Max Lift, Max Flow Rate is 600 L/H, 12' Cord, 2.71" L x 2" W x 2.48" H, 12 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SINGLE-LED	
CW97001	Fountain	P-WP1500	6.7' Max Lift, Max Flow Rate is 2000 L/H, 12' Cord, 6.57" L x 2.95" W x 4.09" H, 45 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SINGLE-LED	

CW97031	Fountain	P-WP2350		13.8' Max Lift, Max Flow Rate is 2350 L/H, 12' Cord, 4.17" L x 2.95" W x 4.09" H, 60 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SIX-LED		
CW97090	Fountain	P-PP333LV	QQ The Fund The Fund The Fund The Start The St	2.5' Max Lift, Max Flow Rate is 250 L/H, 12' Cord, 1.89" L x 1.73" W x 1.14" H, 2.5 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SINGLE-LED	N	
CW11005	Fountain	P-WP1500		6.7' Max Lift, Max Flow Rate is 2000 L/H, 12' Cord, 6.57" L x 2.95" W x 4.09" H, 45 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SINGLE-LED		
CW11134	Fountain	P-PP333LV	A constraint of the second sec	2.5' Max Lift, Max Flow Rate is 250 L/H, 12' Cord, 1.89" L x 1.73" W x 1.14" H, 2.5 Watts, 110V/60Hz AC UL approved	4 COLOR LED		

CW11013	Fountain	PP-P-PP388	Jetanon Marina and Santa and S	4.3' Max Lift, Max Flow Rate is 600 L/H, 12' Cord, 2.71" L x 2" W x 2.48" H, 12 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SINGLE-LED	
CW11030	Fountain	P-SP3000T	TR A	13.7' Max Lift, Max Flow Rate is 4000 L/H, 12' Cord, 4.96" L x 3.74" W x 4.88" H, 99 Watts, 110V/60Hz AC UL approved	2 P-QFOUN-SIX-LED	
CW11032	Fountain	P-WP5000N		19.6' Max Lift, Max Flow Rate is 5000 L/H, 12' Cord, 8.18" L x 4.29" W x 5.12" H, 190 Watts, 110V/60Hz AC UL approved	6 P-QFOUN-SIX-LED	
CW11072	Fountain	P-PP399		5.9' Max Lift, Max Flow Rate is 1000 L/H, 12' Cord, 3.46" L x 2.83" W x 3.18" H, 16 Watts, 110V/60Hz AC UL approved	1 P-QFOUN-SIX-LED	

CW11126	Fountain	P-WP350-SF	2.7' Max Lift, Max Flow Rate is 350 L/H, 12' Cord, 2.24" L x 1.61" W x 1.81" H, 6 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SINGLE-LED	
CW11083	Fountain	P-WP2000	11.8' Max Lift, Max Flow Rate is 2000 L/H, 12' Cord, 4.17" L x 2.95" W x 4.01" H, 45 Watts, 110V/60Hz AC UL approved	2 P-QFOUN-SIX-LED	
CW11027	Fountain	P-WP2350	13.8' Max Lift, Max Flow Rate is 2350 L/H, 12' Cord, 4.17" L x 2.95" W x 4.09" H, 60 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SIX-LED	
CW22025	Fountain	P-WP1500	6.7' Max Lift, Max Flow Rate is 2000 L/H, 12' Cord, 6.57" L x 2.95" W x 4.09" H, 45 Watts, 110V/60Hz AC UL approved	2 P-QFOUN-SIX-LED	

CW22036	Fountain	P-WP2000		11.8' Max Lift, Max Flow Rate is 2000 L/H, 12' Cord, 4.17" L x 2.95" W x 4.01" H, 45 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SIX-LED	
CW22073	Fountain	P-WP650	A Construction of the second sec	5.5' Max Lift, Max Flow Rate is 700 L/H, 12' Cord, 2.79" L x 2" W x 2.24" H, 10 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SINGLE-LED	
CW22035	Fountain	WPP-PP399		5.9' Max Lift, Max Flow Rate is 1000 L/H, 12' Cord, 3.46" L x 2.83" W x 3.18" H, 16 Watts, 110V/60Hz AC UL approved	2 P-QFOUN-SIX-LED	
CW22008	Fountain	WPP-PP399		5.9' Max Lift, Max Flow Rate is 1000 L/H, 12' Cord, 3.46" L x 2.83" W x 3.18" H, 16 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SINGLE-LED	
CW08014	Fountain	WPP-PP399		5.9' Max Lift, Max Flow Rate is 1000 L/H, 12' Cord, 3.46" L x 2.83" W x 3.18" H, 16 Watts, 110V/60Hz AC UL approved	3 P-QFOUN-SINGLE-LED	



WE HAVE ONLY 2 KIND OF LED, ONE IS SINGLE LED,





















