

STUDIO

Extra wide-plank PureForm™ Engineered Bamboo Flooring



FINE BAMBOO FLOORING, PANELS & WORKTOPS

Our classic PureForm™ bamboo in wider, longer, square-edged planks for a look that compliments high ceilings and large spaces. The patented construction employs a cross-ply bamboo fiber core to ensure that the flooring remains flat and the locking system profile strong and stable. The recommended underlayment also creates an acoustic barrier, making Studio ideal for offices or high-rise condominiums, as well as residential homes.



FEATURES + BENEFITS

PERFORMANCE

- Durable 7-step UV Cured Polyurethane coating with aluminum oxide wear layer for abrasion resistance
- Premium PureForm bamboo – 40% harder than oak
- Optimum 5.5 Moso Bamboo: Harvested at maturity for peak density, creating a harder and more stable product for lasting beauty and performance
- Approved for installation over radiant heat flooring systems

VALUE

- Lifetime structural warranty; 10-year heavy-use commercial/25-year residential finish warranties

ECOSMART

- Certified USDA BioPreferred – 99% biobased content
- FSC-certified material available upon request*


INDOOR AIR QUALITY

- Floorscore certified for superior indoor air quality.
- Qualifies for Collaborative for High Performance Schools 2009 Criteria EQ2.2.3 – Low Emitting Materials



PRODUCT DETAILS

Nominal Dimensions :	75" x 7.68" x 0.55" 1905mm x 195mm x 13.97mm
Construction:	Cross-ply Engineered PureForm™ Traditional Bamboo
Milling:	Square Edge
Profile:	Self Locking
Accessories:	Full line of coordinating 14mm accessories
Color Variation:	Most




Valinge-patented self-locking system

INSTALLATION + CARE

Installation Environment:	Float installation into environments having 35-55% RH. Can be installed over radiant heat.
Float Installation:	On, Above or Below grade. Use a vapor barrier with pad over cement subfloor OR vapor retarder with pad over wood subfloor.
Acclimation:	Minimum of 48 hours on-site in box
Maintenance:	BonaKemi Pro Series Hardwood Floor Cleaner or equal

LEED® CREDITS

- IEQ 4.3 Low Emitting Materials
- MR6 Rapidly Renewable Materials
- Certified Wood: MR7 – *available upon request



Flat Grain Natural

Flat Grain Caramelized



Vertical Grain Natural

Vertical Grain Caramelized