SYNERGY® MPL

Narrow-plank Xcora™ Strand Solid Bamboo Flooring



FINE BAMBOO FLOORING, PANELS & WORKTOPS

Teragren's best selling narrow-plank profile combined with our Xcora™ strand bamboo comes in Multiple Precise Lengths of 2,3,4 and 6 feet for an intentionally random visual when installed. Featuring a tongue and groove profile for flexible installation. Designed for use in commercial and residential interiors.



FEATURES + BENEFITS

PERFORMANCE

- Durable 9-step UV Cured Polyurethane coating with aluminum oxide wear layer for abrasion resistance
- Premium Xcora strand bamboo 160% harder than oak
- Optimum 5.5 Moso Bamboo: Harvested at maturity for peak density, creating a harder and more stable product for lasting beauty and performance
- · Approved for installation over radiant heat flooring systems

• Lifetime structural warranty; 10-year heavy-use commercial/25-year residential finish warranties

ECOSMART

Certified USDA BioPreferred – 94% biobased content

INDOOR AIR QUALITY

- Floorscore certified for superior indoor air quality.
- Qualifies for Collaborative for High Performance Schools 2009 Criteria EQ2.2.3 Low **Emitting Materials**

SYNERGY® Java

LEED® CREDITS

- IEQ 4.3 Low Emitting Materials
- MR6 Rapidly Renewable Materials

PRODUCT DETAILS


Nominal Dimensions: 24, 36, 48 & 72" x 3.78" x 0.47"

610mm, 915mm, 1220mm & 1830mm x 96mm x 12mm

Solid Xcora™ Strand Bamboo Construction: Milling: 4 side micro-bevel Profile: Tongue and groove

Accessories: Full line of coordinating 12mm accessories

Color Variation: Moderate



INSTALLATION + CARE

Installation Environment: Nail or Glue installation into environments having 35-55% RH. Can be

installed over radiant heat.

On or Above grade. Use vapor retarder over wood subfloor. Nail Installation:

Glue Installation: On or Above grade. Use a vapor barrier over cement subfloor OR vapor

retarder over wood subfloor.

Recommended Adhesive: **Premium Wood Flooring Adhesive**

18 ga cleat 1 ¼" - 1 ½" Nailing Guidelines:

Acclimation: Minimum of 48 hours on-site in box

BonaKemi Pro Series Hardwood Floor Cleaner or equal Maintenance:





Brindle