

The AndoverTM

FP5220 Series



SPECIFICATION SHEET



Product Specifications Subject To Change

The Andover™ Fan Assembly – FP5220**



Fan Assembly - FP5220**	
Distance from Ceiling to Blade Edge (with 6" DR)	10.3"
Blade Sweep / Pitch	54" / 14°
Down Light Diameter	12"
Canopy Diameter	6½"
Net Hanging Weight: (with Light Kit)	31¼ lbs

Dimensions shown in inches

Available Finishes	
OB	Oil-Rubbed Bronze with Amber Glass
PW	Pewter with Opal/Frosted Glass

Distance from Ceiling to Bottom of Downlight	
Fan w/6" downrod	18"
Fan w/12" downrod	24"
Fan w/18" downrod	30"
Fan w/24" downrod	36"
Fan w/36" downrod	48"
Fan w/48" downrod	60"
Fan w/60" downrod	72"
Fan w/72" downrod	84"

INSTALLATION REQUIREMENTS:

Ceiling fan attaches to electrical junction box securely anchored and capable of withstanding a load of at least 50 lbs.

ELECTRICAL REQUIREMENTS:

Ceiling fan requires a grounded electrical supply line of 120 volts AC, 60 Hz, 15 amp circuit.

MOTOR SPECS:

188 x 20 motor is designed for optimal performance with this fan.

FAN SPEEDS:

3 fan speeds with reversing switch (on top of the motor). High – 145 rpm; Med – 105 rpm; Low – 70 rpm

CONTROL OPTIONS:

The hand-held remote control (C24) with canopy receiver (RECFP5220) is included. Push button remote control will consist of 3 separate fan speeds, infinite light levels, and off position. Reversing switch located on fan housing. Optional wall control (C25) is available (to be used in conjunction with fan receiver).

LIGHTING OPTIONS:

The 3-bulb (40 watt max candelabra bulbs - not included) downlight fixture is included with this fan assembly. Maximum downlight wattage not to exceed 120 watts.

DOWNROD OPTIONS:

The Andover™ fan comes with a 1" Dia. x 6" (DR1-6) & 12" (DR1-12) downrods and decorative downrod sleeve. Optional downrods are available in 18", 24", 36", 48", 60", and 72". For installations requiring a longer downrod, a downrod coupler is available. The Andover™ fan can be mounted on a sloped ceiling up to 30°. Most sloped ceiling installations require a downrod longer than the standard 6" downrod. Optional sloped ceiling ball kits (SCB1-52) are available for up to 52°. Call tech support for more information.

BLADE SETS:

A set of 5 reversible (cherry/walnut) wood blades are included. Not recommended for Damp Location.

DAMP LOCATION:

Fan not rated for Damp Location usage.



**10983 Bennett Parkway
Zionsville, IN 46077
Toll Free (888) 567-2055
FAX (866) 482-5215**

**Outside U.S. call (317) 733-4113
Visit Our Website www.fanimation.com**

