

HL10000 SERIES® PEDESTAL SPECIFICATIONS

GENERAL INFORMATION:

Hirsh's HL10000 Series® pedestals are commercial grade, steel products. They are available in box/box/file, file/file and box/file drawer configurations, 19", 19.88", 22", and 22.88" depths. Two handle styles are available: full width J-pull and monochrome recessed pull. These files are designed to accept letter size hanging folders. Each drawer suspension utilizes a pair of high quality, commercial grade, steel ball-bearing slides. These slides allow, smooth, quiet and full drawer extension while exceeding all applicable BIFMA test requirements. Each file comes complete with a core removable locking system. Mobile pedestals include 4 casters (two swivel and two fixed). Casters are factory installed. Mobile units include counterweights for stability. Fixed units include four leveling glides.

CABINET DIMENSIONS:

Depths:

Recessed Pull – 19.00" & 22.00"

Full Width Pull – 19.88" & 22.88"

Heights:

Fixed/Work Surface Supporting:

Box/Box/File & File/File: 27 1/4" (glides extend up to 1" for leveling)

Mobile:

Box/Box/File & File/File: 27-3/4"

Box/File: 21-3/4"

Width: 15"

CABINET CONSTRUCTION:

The file case shell is fully enclosed and features a one piece side-back-side construction. The top panel and the fully enclosed base are assembled using resistance welds and MIG welds. A front and rear steel post extending the height of the cabinet, are resistance welded and MIG welded to each internal side of the case wrapper.

DRAWER CONSTRUCTION:

The drawers are constructed from a one-piece Side/Bottom/Side Body. A back plate is resistance welded at both sides and across the drawer bottom. The drawer front interlocks with the drawer bottom along the entire width of the drawer.

STEEL GAUGE SPECIFICATIONS:HL10000 Series®**Cabinet:**

Top Panel	22 gauge
Bottom Panel	20 gauge
Side-Back-Side	25 gauge
Vertical Reinforcement Posts	24 gauge
Lock Bars	16 gauge

Drawers:

Drawer Front	24 gauge
Side-Bottom-Side	24 gauge
Back Panel	24 gauge

SUSPENSION:

Three-piece, steel ball-bearing slides are utilized, for ultimate suspension performance. This suspension exceeds ANSI/BIFMA requirements.

LOCK FEATURES:

For excellent security, a barrel style lock with removable core and two keys come standard with each cabinet. Master keys are available upon request.

FINISH:

All post-painted metal components complete a three-stage power wash system, washing and treating each component with an iron phosphate conversion coating. An industrial grade baking enamel is then applied and baked for a durable and long lasting finish.

PERFORMANCE:

Meets or exceeds all applicable BIFMA tests.

WARRANTY:

Hirsh Industries offers a Limited Lifetime Warranty on all of our HL10000 Series® Pedestals.