



HIGH GLOSS
COLLECTION
—by Somerset™—



Natural Red Oak
(Red Oak)



Butterscotch
(Red Oak)



Gunstock
(Red Oak)



Cherry Oak
(Red Oak)



Natural White Oak
(White Oak)



Chestnut
(White Oak)



Spice
(White Oak)

APPALACHIAN OAK FLOORING IN A RANGE
OF POPULAR COLORS, FOR THOSE WHO
PREFER A GLOSSIER FINISH.



S SOLID
3/4" thick; random lengths

WIDTHS: 2-1/4", 3-1/4"

e ENGINEERED
1/2" thick, solid sawn face; 8 plies;
random lengths

WIDTHS: 3-1/4", 5"



PRODUCT SPECIFICATION SHEET

06/12

HIGH GLOSS: SOLID



Product:	Somerset High Gloss Collection Solid Hardwood Flooring		
Species:	Red Oak or White Oak (Somerset does not mix species.)		
Grade:	Proprietary Somerset grade that meets or exceeds NOFMA Standard and Better.		
Dimensions:	Thickness: 3/4"* Widths: 2-1/4", 3-1/4" Lengths: Random up to 6-1/2' (conforms to NOFMA Standard and Better specification) <small>*Nominal</small>		
Construction:	Traditional 3/4" solid construction produced from domestically grown and harvested Appalachian hardwood. Material conforms to Appalachian Hardwood Manufacturers Inc.'s Verified Sustainable Seal (http://www.appalachianwood.org). Product is also affiliated with National Oak Flooring Manufacturers Association and the National Wood Flooring Association.		
Profile:	Eased Edge, Square End		
Finish:	Ultimate™ Urethane Finish — UV Cured Aluminum Oxide, Abrasion Resistant Finish		
Colors:	2 1/4" Width	3 1/4" Width	Species
	Natural Red Oak	PS2601HG PS3601HG	Red Oak
	Butterscotch	PS2603HG PS3603HG	Red Oak
	Gunstock	PS2604HG PS3604HG	Red Oak
	Cherry Oak	PS2605HG PS3605HG	Red Oak
	Natural White Oak	PS2606HG PS3606HG	White Oak
	Chestnut	PS2607HG PS3607HG	White Oak
	Spice	PS2608HG PS3608HG	White Oak
Gloss Level:	High Gloss		
Janka Hardness:	Species	Lbs	
	Red Oak	1290	
	White Oak	1360	
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request		
Flame Spread:	Class C		
Installation:	Nail down or staple, on or above grade. (NWFA Installation Guidelines and Methods, Revised March 2007). Installation guidelines are printed on the bottom of each carton and available at Somersetfloors.com .		
Maintenance:	Somerset Ultimate™ Wood Floor Cleaner (www.somersetfloors.com)		
Limited Warranty:	50-Year Finish Wear; Lifetime Structural Integrity (www.somersetfloors.com)		
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer		



PRODUCT SPECIFICATION SHEET

06/12

HIGH GLOSS: ENGINEERED



Product:	Somerset High Gloss Collection Engineered Hardwood Flooring			
Species:	Red Oak or White Oak (Somerset does not mix species.)			
Grade:	Proprietary Somerset grade that meets or exceeds NOFMA Standard or Better.			
Dimensions:	Thickness: 1/2"*; 3mm* dry sawn face Widths: 3-1/4", 5" Lengths: Random up to 6-1/2' <small>*Nominal</small>			
Construction:	8 ply cross grain engineered construction; 7 ply birch core.			
Profile:	Eased Edge, Eased End			
Finish:	Ultimate™ Urethane Finish — UV Cured Aluminum Oxide, Abrasion Resistant Finish			
Colors:	3/4" Width	5" Width	Wear Layer Species	
	Natural Red Oak	EP3601HGE	EP5601HGE	Red Oak
	Butterscotch	EP3603HGE	EP5603HGE	Red Oak
	Gunstock	EP3604HGE	EP5604HGE	Red Oak
	Cherry Oak	EP3605HGE	EP5605HGE	Red Oak
	Natural White Oak	EP3606HGE	EP5606HGE	White Oak
	Chestnut	EP3607HGE	EP5607HGE	White Oak
	Spice	EP3608HGE	EP5608HGE	White Oak
Gloss Level:	High Gloss			
Janka Hardness:	Species	Lbs		
	Red Oak	1290		
	White Oak	1360		
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request			
Flame Spread:	Class C			
Installation:	Nail, staple, glue down, or float on, above or below grade (ground level). (NWFA Installation Guidelines and Methods, Revised March 2007). Installation guidelines are printed on the bottom of each carton and available at Somersetfloors.com.			
Maintenance:	Somerset Ultimate™ Wood Floor Cleaner (www.somersetfloors.com)			
Limited Warranty:	50-Year Finish Wear; Lifetime Structural Integrity (www.somersetfloors.com)			
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer			