









Natural Red Oak Ha (Red Oak) (W



Harvest Oak (White Oak)



Golden Oak (Red Oak)



Gunstock (White Oak)



Cherry Oak (Red Oak)



Mocha (Red Oak)



Metro Brown (White Oak)



COLOR YOUR SPACE WITH APPALACHIAN OAK FLOORING. CHOOSE FROM A RANGE OF

COLORS, IN STRIP AND PLANK WIDTHS.



3/4" thick; random lengths

WIDTHS: 4", 5"



1/2" thick, solid sawn face; 8 plies; random lengths

WIDTHS: 3-1/4", 5"



PRODUCT SPECIFICATION SHEET

06/12

COLOR PLANK: SOLID



COLON	I LAININ. SOLIL	,					
Product:	Somerset Color Collection Plank Solid	l Hardwood Flooring					
Species:	Red Oak or White Oak (Somerset does not mix species.)						
Grade:	Proprietary Somerset grade that meets or exceeds NOFMA Standard and Better.						
Dimensions:	Thickness: 3/4"* Widths: 4", 5" Lengths: Random up to 6-1/2' (conforms to NOFMA Standard and Better specification) *Nominal						
Construction:	Traditional 3/4" solid construction produced from domestically grown and harvested Appalachian hardwood. Material conforms to Appalachian Hardwood Manufacturers Inc.'s Verified Sustainable Seal (www.appalachianwood.org). Product is also affiliated with National Oak Flooring Manufacturers Association and the National Wood Flooring Association.						
Profile:	Eased Edge, Square End						
Finish:	Ultimate™ Urethane Finish — UV Cured Aluminum Oxide, Abrasion Resistant Finish						
Colors:	Natural Red Oak Harvest Oak Golden Oak Gunstock Cherry Oak Mocha Metro Brown	4" Width PP41RO PP41HO PP41GO PP41GU PP41CO PP41MO PP41MB	5" Width PP51RO PP51HO PP51GO PP51GU PP51 CO PP51MO PP51MB	Species Red Oak White Oak Red Oak White Oak Red Oak Red Oak Red Oak Red Oak White Oak			
Gloss Level:	Semi Gloss						
Janka Hardness:	SpeciesLbsRed Oak1290White Oak1360						
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request						
Flame Spread:	Class C						
Installation:	Nail down or staple, on or above grade. (NWFA Installation Guidelines and Methods, Revised March 2007). Installation guidelines are printed on the bottom of each carton and available at Somersetfloors.com.						
Maintenance:	Somerset Ultimate [™] Wood Floor Cleaner (www.somersetfloors.com)						
Limited Warranty:	50-Year Finish Wear; Lifetime Structural Integrity (www.somersetfloors.com)						
Molding:	Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer						



PRODUCT SPECIFICATION SHEET

06/12

COLOR PLANK: ENGINEERED



COLON	I LAINIX. LIN			9		
Product:	Somerset Color Collection Engi	neered Hardwood Flo	oring			
Species:	Red Oak or White Oak (Somerset does not mix species.)					
Grade:	Proprietary Somerset grade that meets or exceeds NOFMA Standard or Better.					
Dimensions:	Thickness: 1/2"*; 3mm* dry sawn face Widths: 3-1/4", 5" Lengths: Random up to 6-1/2' *Nominal					
Construction:	8 ply cross grain engineered cor	struction; 7 ply birch (core.			
Profile:	Eased Edge, Eased End					
Finish:	Ultimate™ Urethane Finish — UV Cured Aluminum Oxide, Abrasion Resistant Finish					
Colors:	Offinial Offinial Ov	31/4" Width	5" Width	Wear Layer Species		
	Natural Red Oak	EP314ROE	EP512ROE	Red Oak		
	Harvest Oak	EP314HOE	EP512HOE	White Oak		
	Golden Oak	EP314GOE	EP512GOE	Red Oak		
	Gunstock	EP314GUE	EP512GUE	White Oak		
	Cherry Oak	EP314COE	EP512COE	Red Oak		
	Mocha	EP314MOE	EP512MOE	Red Oak		
	Metro Brown	EP314MBE	EP512MBE	White Oak		
Gloss Level:	Semi Gloss					
Janka Hardness:	SpeciesLbsRed Oak1290White Oak1360					
MSDS:	Not required for cured finish, MSDS for Wood Dust available on request					
Flame Spread:	Class C					
Installation:	Nail, staple, glue down, or float on, above or below grade (ground level). (NWFA Installation Guidelines and Methods, Revised March 2007). Installation guidelines are printed on the bottom of each carton and available at Somersetfloors.com.					
Maintenance:	Somerset Ultimate [™] Wood Floor Cleaner (www.somersetfloors.com)					
Limited Warranty:	50-Year Finish Wear; Lifetime Str	uctural Integrity (www	ı.somersetfloors.com	n)		
Molding:	Quarter Round, Stair Nose, Thre	shold, T-Mold, and Re	educer			