



Hickory Natural (Hickory)



Hickory Natural (Hickory)



Hickory Natural (Hickory)



Hickory Natural (Hickory)



Hickory Natural (Hickory)



Hickory Natural (Hickory)



Hickory Natural (Hickory)

MAKE A STATEMENT WITH APPALACHIAN HICKORY AND MAPLE FLOORING—BEAUTIFUL ALTERNATIVES TO TRADITIONAL OAK FLOORING.



S SOLID
3/4" thick; random lengths

WIDTHS: 2-1/4" (maple), 3-1/4", 4", 5"

E ENGINEERED
1/2" thick, solid sawn face; 8 plies; random lengths

WIDTHS: 3-1/4", 5"



PRODUCT SPECIFICATION SHEET

06/12

SPECIALTY: SOLID



| | | | | | | |
|-------------------|---|---------------------------|---------------------------|-----------------------|-----------------------|----------------|
| Product: | Somerset Specialty Collection Solid Hardwood Flooring | | | | | |
| Species: | Hickory or Hard Maple | | | | | |
| Grade: | Proprietary Somerset grade that meets or exceeds NOFMA Standard and Better. | | | | | |
| Dimensions: | Thickness: 3/4"* Widths: Hickory; 3-1/4", 4", 5" Maple; 2-1/4", 3-1/4", 4", 5" Lengths: Random up to 6-1/2' (conforms to NOFMA Standard and Better specification) <small>*Nominal</small> | | | | | |
| Construction: | Traditional 3/4" solid construction produced from domestically grown and harvested Appalachian hardwood. Material conforms to Appalachian Hardwood Manufacturers Inc.'s Verified Sustainable Seal (www.appalachianwood.org). Product is also affiliated with National Oak Flooring Manufacturers Association and the National Wood Flooring Association. | | | | | |
| Profile: | Eased Edge, Square End | | | | | |
| Finish: | Ultimate™ Urethane Finish — UV Cured Aluminum Oxide, Abrasion Resistant Finish | | | | | |
| Colors: | | 2 1/4" Width Strip | 3 1/4" Width Strip | 4" Width Plank | 5" Width Plank | Species |
| | Hickory Natural | | PS314HC | PP41HC | PP51HC | Hickory |
| | Hickory Nutmeg | | PS314HNU | PP41HNU | PP51HNU | Hickory |
| | Hickory Spice | | PS314HSP | PP41HSP | PP51HSP | Hickory |
| | Maple Natural | PS5101 | PS51401 | PP41MP | PP51MP | Hard Maple |
| | Maple Canyon Brown | PS5119 | PS51419 | PP41CBM | PP51CBM | Hard Maple |
| | Maple Cherry | PS5109 | PS51409 | PP41CHM | PP51CHM | Hard Maple |
| | Maple Tumbleweed | PS5110 | PS51410 | PP41TUM | PP51TUM | Hard Maple |
| Gloss Level: | Semi Gloss | | | | | |
| Janka Hardness: | Species | Lbs | | | | |
| | Hickory | 1820 | | | | |
| | Hard Maple | 1450 | | | | |
| MSDS: | Not required for cured finish, MSDS for Wood Dust available on request | | | | | |
| Flame Spread: | Class C | | | | | |
| Installation: | Nail down, or staple, on or above grade. (NWFA Installation Guidelines and Methods, Revised March 2007). Installation guidelines are printed on the bottom of each carton and available at Somersetfloors.com . | | | | | |
| Maintenance: | Somerset Ultimate™ Wood Floor Cleaner (www.somersetfloors.com) | | | | | |
| Limited Warranty: | 50-Year Finish Wear; Lifetime Structural Integrity (www.somersetfloors.com) | | | | | |
| Molding: | Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer | | | | | |



PRODUCT SPECIFICATION SHEET

06/12

SPECIALTY: ENGINEERED



| | | | | |
|-------------------|--|-----------------|---------------------------|------------|
| Product: | Somerset Specialty Collection Engineered Hardwood Flooring | | | |
| Species: | Hickory or Hard Maple | | | |
| Grade: | Proprietary Somerset grade that meets or exceeds NOFMA Standard or Better. | | | |
| Dimensions: | Thickness: 1/2"*; 3mm* dry sawn face Widths: 3-1/4", 5" Lengths: Random up to 6-1/2' <small>*Nominal</small> | | | |
| Construction: | 8 ply cross grain engineered construction; 7 ply birch core. | | | |
| Profile: | Eased Edge, Eased End | | | |
| Finish: | Ultimate™ Urethane Finish — UV Cured Aluminum Oxide, Abrasion Resistant Finish | | | |
| Colors: | 3 1/4" Width | 5" Width | Wear Layer Species | |
| | Hickory Natural | EP314SPHCE | EP512SPHCE | Hickory |
| | Hickory Nutmeg | EP314HNUE | EP512HNUE | Hickory |
| | Hickory Spice | EP314HSPE | EP512HSPE | Hickory |
| | Maple Natural | EP314SPMPE | EP512SPMPE | Hard Maple |
| | Maple Canyon Brown | EP314CBME | EP512CBME | Hard Maple |
| | Maple Cherry | EP314CHME | EP512CHME | Hard Maple |
| | Maple Tumbleweed | EP314TUME | EP512TUME | Hard Maple |
| Gloss Level: | Semi Gloss | | | |
| Janka Hardness: | Species | Lbs | | |
| | Hickory | 1820 | | |
| | Hard Maple | 1450 | | |
| MSDS: | Not required for cured finish, MSDS for Wood Dust available on request | | | |
| Flame Spread: | Class C | | | |
| Installation: | Nail, staple, glue down, or float on, above or below grade (ground level). (NWFA Installation Guidelines and Methods, Revised March 2007). Installation guidelines are printed on the bottom of each carton and available at Somersetfloors.com. | | | |
| Maintenance: | Somerset Ultimate™ Wood Flooring Cleaner (www.somersetfloors.com) | | | |
| Limited Warranty: | 50-Year Finish Wear; Lifetime Structural Integrity (www.somersetfloors.com) | | | |
| Molding: | Quarter Round, Stair Nose, Threshold, T-Mold, and Reducer | | | |