

ESDQ SERIES

RANGE HOODS

ENERGY STAR® Deluxe Quiet Under Cabinet Range Hood

Dimensions

Overall bottom projection - 18.38"

Height -12.38" Width: 30"

• Body

Stainless Steel or 23 gauge cold rolled steel, auto welded, powder coated

Lighting

Electronic Quick Start Ballast – Use Triple 4 pin PL lamp, maximum 26 Watts.

Ducting Options

Horizontal ducting: 3.25"x10" (duct adapter and damper included)

Vertical ducting: 3.25"x10" (duct adapter and damper included)

Ductless: removable front vent (charcoal filter not included)

Filters

Dishwasher safe, aluminum mesh grease filters (included).

Available Finishes

Stainless Steel, White, Black


Motor


3 speed, thermally protected, permanently lubricated motor. Rated 120 volts,60 hz. with two electronically balanced blower wheels

PERFORMANCE: High - 270 CFM @ 4.0 Sones, HVI Certified

Medium - 200 CFM @ 2.5 Sones, HVI Certified

Low (Normal Operating Speed) - 150 CFM @ 1.5 Sones, HVI Certified





		CFM	SONES		DUCT			
MODEL	COLOR	HIGH/MED/LOW	HIGH/MED/LOW	LIGHTING	SIZE	WIDTH	HEIGHT	DEPTH
ESDQ1308	Stainless Steel	270/200/150	4.0/2.5/1.5	26W Fluorescent	3.25" x 10"	30"	7.5"	18"
ESDQ1303	White	270/100/150	4.0/2.5/1.5	26W Fluorescent	3.25" x 10"	30"	7.5"	18"
ESDQ1306	Black	270/200/150	4.0/2.5/1.5	26W Fluorescent	3.25" x 10"	30"	7.5"	18"

PROJECT							ARCHITECT			
LOCATION							ENGINEER			
CONTRACTOR							SUBMITTED BY DATE			
FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	ОТУ	OPTIONAL EQUIPMENT & REMARKS	







U.S.: West Chester, PA 19380 Phone: (877) 304-3785

Fax: (610) 696-8048

Email: sales@airkinglimited.com

Canada: Brampton, Ontario L6T 2J3

Phone: (905) 456-2033 Fax: (905) 456-1015

Email: casales@airkinglimited.com