

Natural

Almada Technical Specifications

Description: Glueless Drop & Lock cork floating floor

Warranty: **Lifetime Limited Residential Wear Warranty**

Lifetime Structure Warranty

5 Year Limited Light/Medium Commercial Wear Warranty

Species: Cork

Float Installation:

Size/Packaging: $4 \frac{1}{8}$ " × 35 $\frac{5}{8}$ " × 13/32" (24.49 sq. ft/carton, 43 lbs.)

Component Thickness: Top cork layer – 3 mm

HDF layer - 6 mm

Bottom cork layer - 2 mm

Endura AR™ UV-cured finish with advanced abrasion resistance Finish:

Passes "Life Safety Codes" Flammability:

Flaming: 199 / Non-Flaming: 177 Smoke Density:

[ASTM E 662-05]

Critical Radiant Flux: .23 watts/cm²

[ASTM E648-06]

IIC Impact Insulation: 58

[ASTM E492-04]

STC Sound Transmission: 54

[ASTM E413-87]

Moisture Content: > 6 to < 9%

Certifications: GREENGUARD® Children & Schools Certification

> **CARB Compliant Lacey Act Compliant**

Environmental Statement: USFloors' commitment is to provide consumers and specifiers with beautiful and

durable floors at a good value, while minimizing our impact on the environment

and enhancing and improving it whenever possible.

USFloors is a member of the USGBC.

Country of Origin: Components manufactured in Portugal. Finished with pride in the USA.