

Manufacturer of Unique and Sustainable Floors

Natural CORK

®

New Earth Technical Specifications

Description: Glueless Drop & Lock cork floating floor

Warranty: Lifetime Limited Residential Wear Warranty

Lifetime Structure Warranty

5 Year Limited Light/Medium Commercial Wear Warranty

Species: Cork

Installation: Float

Size/Packaging: 4 1/8" × 35 5/8" × 13/32" (24.49 sq. ft/carton, 43 lbs.)

Component Thickness: Top cork layer – 3 mm

HDF layer - 6 mm

Bottom cork layer - 2 mm

Finish: Endura AR™ UV-cured finish with advanced abrasion resistance

Flammability: Passes "Life Safety Codes"

Smoke Density: Flaming: 199 / Non-Flaming: 177

[ASTM E 662-05]

Critical Radiant Flux: .23 watts/cm²

[ASTM E648-06]

IIC Impact Insulation: 58

[ASTM E492-04]

STC Sound Transmission: 54

[ASTM E413-87]

Moisture Content: > 6 to < 9%

Certifications: GREENGUARD® Children & Schools Certification

CARB Compliant Lacey Act Compliant

Environmental Statement: USFloors' commitment is to provide consumers and specifiers with beautiful and

durable floors at a good value, while minimizing our impact on the environment

and enhancing and improving it whenever possible.

USFloors is a member of the USGBC.

Country of Origin: Components manufactured in Portugal. Finished with pride in the USA.