



## PRODUCT INFORMATION

# BOSTIK'S ULTIMATE™ ADHESIVE REMOVER

Removes Wet and Cured Urethanes from Pre-Finished, Non-Wax Wood Flooring

### PRODUCT DESCRIPTION

Bostik's Ultimate™ Adhesive Remover is a readily biodegradable, low odor, water rinseable solution. Use Ultimate to remove wet and cured urethane adhesive from the surface of pre-finished (non-wax) wood flooring.

### DIRECTIONS FOR USE

Bostik's Ultimate Adhesive Remover is available in a liquid formulation as well as pre-soaked, ready-to-use towels. NOTE: To insure product satisfaction, always test a small area prior to application.

### APPLICATION (LIQUID FORMULATION)

1. Apply remover to a dry, clean, non-abrasive cloth.
2. Using the dampened cloth, wipe area of the floor that has cured or wet adhesive.
3. If adhesive has cured for more than two days, apply a **small** amount of Ultimate Urethane Remover directly on the adhesive and let it stand approximately 5 minutes. Wipe area clean with a dry cloth. **NOTE: Do not allow remover to drip between floor boards.**

### APPLICATION (PRE-SOAKED TOWELS)

1. Open lid and pull out towels.
2. Rub area of the floor that has cured or wet adhesive using a pre-soaked towel.
3. If adhesive has cured for more than two days, lay a towel over cured adhesive and let it stand for approximately 5 minutes. Wipe area clean with a fresh towel. **NOTE: Do not allow excess remover to drip between floor boards.**

### LIMITED WARRANTY

Bostik, Inc. warrants that the product conforms with Bostik's written specifications and is free from manufacturing defects. A PURCHASER'S SOLE REMEDY FOR NONCOMPLIANCE WITH THIS WARRANTY SHALL BE THE REPLACEMENT OF THE PRODUCT OR REFUND OF THE PURCHASE PRICE. Purchasers may address their warranty claims to Bostik, Inc., 211 Boston St., Middleton, MA 01949, Attn: Customer Service or call Bostik at 1-800-7/BOSTIK. TO THE MAXIMUM EXTENT ALLOWED BY LAW, BOSTIK DISCLAIMS ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND LIABILITY FOR DIRECT, INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitations may not apply to you. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

### CHEMICAL & PHYSICAL PROPERTIES

Appearance	Light Yellow
Odor	Citrus
Approximate Boiling Point	>350°F
DOT Hazard Class	Not a Regulated Material
Proper Name	Cleaning Compound, NOS
pH	7
Flash point	205∞F
Flammability	Non-flammable
V.O.C. Content	< 10 grams/liter

### STORAGE/SHELF LIFE

Store Ultimate Adhesive Remover in a clean, dry area. Shelf life is one year from date of manufacturing.

### PACKAGING

Available in 32 fl. oz. containers. For the name of a distributor near you, contact a Bostik Customer Service Representative at 1-800-7/BOSTIK.



Middleton, MA 01949  
1-800-7/BOSTIK  
1-800-726-7845

www.bostik-us.com



### PLANT LOCATIONS

Temecula, CA 92590  
Conyers, GA 30207  
Paulsboro, NJ 08066



09300

9

Wood Flooring  
Urethane Adhesive Remover

June 2006. Supersedes all previously published literature.

