MATERIAL SAFETY DATA SHEET Used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200 SECTION I - NAME AND PRODUCT Flexovit East U.S.A., Inc. 154 Potomac Ave., Unit A Tallmadge, Ohio 44278				Flammability Rating Health Rating 1 x x x					
Phone: (800) 321-8800 Fax: (888) 321-8800									
Updated: 5/99				Hazard Rating					
Product: All Type 27, 28, 29, and Type 1 wheels									
including Flexon, Flexcel, and Speedoflex products.			NFPA HAZARD RATING CODE						
	S	ECTION II	- CO	MPOSITIO	N				
	% By	OSHA			OSHA	ACGIH	Other	Carcin-	
Ingredient	Weight	Regulate	(Cas #	PEL	TLV	Limits	ogen	
Aluminum Oxide	60 - 80	No	1344-28-1		NA	10mg/m	N/A	No	
Silicon Carbide	NA	No	40	9-21-2	NA	NA	N/A	No	
Zirconium Oxide	0 - 12	No	1314-23-4		NA	10mg/m	N/A	No	
Calcium Hydroxide	NA	No		N/A	NA	5mg/m	N/A	No	
Barium Sulfate	NA	No		N/A	0.5mg/m	10mg/m	N/A	No	
Iron Sulfide	NA	No	13	17-37-9	NA	NA	N/A	No	
Florides	NA	No	16984-48-8		2.5mg/m	2.5mg/m	N/A	No	
Phenolic Resin	0 - 15	No	9003-35-4		5 P.P.M.	5 P.P.M.	N/A	No	
Fiber Glass	0 - 5	No	N/A		15mg/m	10mg/m	N/A	No	
Aluminum or Steel	0.1 - 1	No		N/A	NA	NA	N/A	No	
Zinc	NA	No		N/A	NA	NA	N/A	No	
SECTIO	on III - Ph	IYSICAL/C	HEM	ICAL CHA	RACTERISTICS	;			
Boiling Point N/A				Specific Gravity (H20=1) 2 - 4					
Vapor Pressure (mm Hg.) N/A			Melting Point N/A						
Vapor Density (AIR=1) N/A			Evaporation Rate (Butyl Acetate=1) N/A						
Solubility in Water Slight			Appearance/Odor Dark colored solid.						
May give off some odor in								lor in use.	
SECTION IV - FIRE AND EXPLOSION DATA									
Means Of Extinction Water or carbon dioxide.				Lower And Upper Explosion Limits				N/A	
Flammable Limits N/A			Special F	ire Fighting Pro	ocedures		None		
Flash Point		N/A		Unusual I	Fire or Explosic	on Hazards		None	

SECTION V - REACTIVITY DATA							
Stable - Avoid excessive moisture, high relative humidity, temperature extremes and contact with acids or solvents							
Not incompatible with any materials							
Hazardous Polymerzation will not occur							
Dust and organic fumes are generated in use. Do not exceed TLV's.							
SECTION VI - HEALTH HAZARD DATA							
Route(s) of Entry	Signs and Symptoms of Exposure	Emergency and First-Aid procedures					
x	May cause coughing and shortness of breath during	Terminate exposure and remove to					
Dust Inhalation	grinding. May affect breathing capacity.	fresh air. Obtain medical assistance.					
Ingestion	No known adverse effects, but not recommended.	Obtain medical assistance.					
Absorption	Not absorbed through skin.	N/A					
	Grinding wheel may cause abrasions. Dust may	Terminate exposure and remove to					
Skin contact	cause skin irritation.	fresh air. Obtain medical assistance.					
Eye	Dust or fumes may cause eye irritation.	Fresh air and medical assistance.					
Other	Excessive noise levels may exist in use.	Cease use. Obtain medical assistance					
Medical conditions	such as emphysema and asthma may be aggravated du	ing grinding.					
SECTION VII- STORAGE HANDLING AND USE PROCEDURES							
Handling and storage procedures - Avoid damage to wheel. Do not drop. Do not use a wheel that has been damage							
or dropped. Avoid excessive temperatures in storage. Always handle in accordance with ANSI B7.1.							
Normal clean up procedures should be used if material is released.							
Dispose of waste in a sanitary landfill in accordance with state, local and federal regulations.							
Always use in accordance with ANSI Z43.1 and OSHA 1910.215. Do not use dropped or damaged wheels. Do not							
use without machine guard in place. Do not exceed maximum RPM on wheel.							
SECTION VIII- CONTROL MEASURES							
Protection	Requirements and Referrals						
Respiratory	OSHA or NIOSH approved respirator if TLV's exceeded. See OSHA 29 CFR 1910.134						
Ventilation	Local and mechanical exhaust recommended. See ANSI Z43.1. Refer to OSHA 29 CFR 1910.9						
Protective Gloves	Not required but use if desired.						
Eye Protection	Required. Refer to OSHA 29 CFR 1910.133.						
Hearing Protection	Required. Refer to OSHA 29 CFR 1910.95.						
Other	Apron and/or face shield if desired.						
Hygienic Practices Wash with soap and water after handling and grinding.							
COMPANY USE							
The information and recommendations set forth herein are taken from sources and references believed to be							
accurate and complete as of the date hereof. However, FlexOvit® U.S.A. Inc. makes no expressed or implied war-							
ranty with respect t	o the accuracy of the information or the suitability of the re	commendations, and assumes no					
liability to any user thereof.							