SUPERSEDES: 04-06-2009

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

COMPANY INFORMATION H.B. Fuller Construction Products Inc. 1105 S. Frontenac Street Aurora, IL 60504 Phone: 1-800-552-6225

> Medical Emergency Phone Number (24 Hours): 1-888-853-1758 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

PRODUCT INFORMATION PRODUCT NUMBER: PRODUCT NAME: PRODUCT DESCRIPTION: PRODUCT IDENTIFIER:

CP2110 CHILDERS CP-211 Coating 801867PM

SECTION 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW PHYSICAL STATE: Liquid COLOR: White ODOR: Sweet Cancer hazard.

POTENTIAL HEALTH EFFECTS BY ROUTE OF ENTRY

EYE: Can cause minor irritation, tearing and reddening.

SKIN: Can cause minor skin irritation, defatting, and dermatitis.

INHALATION: Can cause minor respiratory irritation. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract. Overexposure to crystalline silica may cause silicosis.

This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

INGESTION: Ingestion is not an anticipated route of exposure. No hazard in normal industrial use.

LONG-TERM (CHRONIC) HEALTH EFFECTS TARGET ORGAN(S): Lungs

REGULATED CARCINOGEN STATUS:

Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH, or OSHA listed carcinogens. Crystalline silica

Titanium dioxide

Vinyl acetate

EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE: Lung disease

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS #	PERCENT
Crystalline silica	14808-60-7	10 - 30
Aluminum hydroxide	21645-51-2	10 - 30

Titanium dioxide	13463-67-7	1 - 5
Cellulose	9004-34-6	1 - 5
Vinyl acetate	108-05-4	0.1 - 1

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

SECTION 4: FIRST AID MEASURES

IF IN EYES: Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.

IF ON SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

IF VAPORS INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT:	Non flammable
AUTOIGNITION TEMPERATURE:	Not established
LOWER EXPLOSIVE LIMIT (% in air):	Not established
UPPER EXPLOSIVE LIMIT (% in air):	Not established
EXTINGUISHING MEDIA:	Use water spray, foam, dry chemical or carbon dioxide.
UNUSUAL FIRE AND EXPLOSION HAZARDS:	There is a possibility of pressure buildup in closed containers when heated. Water spray may be used to cool the containers.
SPECIAL FIRE FIGHTING INSTRUCTIONS:	Persons exposed to products of combustion should wear self- contained breathing apparatus and full protective equipment.
HAZARDOUS COMBUSTION PRODUCTS:	Carbon dioxide, Carbon monoxide

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPECIAL PROTECTION:	No adverse health effects expected from the clean-up of spilled material.
	Follow personal protective equipment recommendations found in Section 8
	of this MSDS.
CLEAN-UP:	Dike if necessary, contain spill with inert absorbent and transfer to containers
	for disposal. Keep spilled product out of sewers, watersheds, or water
	systems.
	Avoid creating dusts. Cover material with absorbent and moisten and collect
	for disposal.

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling: No special handling instructions due to toxicity. Avoid breathing material.

Storage: Store in a cool, dry place.

Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION:	Wear safety glasses when handling this product.
SKIN PROTECTION:	Avoid skin contact by wearing chemically resistant gloves.
GLOVES:	Not normally required. Use nitrile gloves if conditions warrant.
RESPIRATORY PROTECTION:	Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. NIOSH approved air purifying respirator with dust/mist filter. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134).
VENTILATION:	Use local exhaust ventilation or other engineering controls to minimize exposures.

EXPOSURE LIMITS:

Chemical Name	ACGIH EXPOSURE LIMITS	OSHA PEL
Crystalline silica	0.025 mg/m3 TWA (respirable fraction)	((250)/(%SiO2 + 5) mppcf TWA (respirable)); ((10)/(%SiO2 + 2) mg/m3 TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust))
Aluminum hydroxide	Not established	Not established
Titanium dioxide	10 mg/m3 TWA	15 mg/m3 TWA (total dust)
Cellulose	10 mg/m3 TWA	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)
Vinyl acetate	10 ppm TWA 15 ppm STEL	Not established

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: COLOR: ODOR: ODOR THRESHOLD: WEIGHT PER GALLON (lbs.): SPECIFIC GRAVITY:	Liquid White Sweet Not established 11.1 1.33
SOLIDS (% by weight):	66.0
pH: FLASH POINT: BOILING POINT (deg. C): FREEZING/MELTING POINT (deg. C): VAPOR PRESSURE (mm Hg): VAPOR DENSITY: EVAPORATION RATE: OCTANOL/WATER COEFFICIENT: VOC, weight percent VOC, EPA Method 24, less water and exempt solvents (theoretically determined)	Not established Non flammable Not established Not established Not established Not established Not established 1.7 39g/liter of material

SECTION 10: STABILITY AND REACTIVITY

STABILITY:

Stable under normal conditions.

CHEMICAL INCOMPATIBILITY:Not establishedHAZARDOUS POLYMERIZATION:Will not occur.HAZARDOUS DECOMPOSITION PRODUCTS:Carbon monoxide, carbon dioxide

SECTION 11: TOXICOLOGICAL INFORMATION

COMPONENT	LD50/LC50
Crystalline silica	Not established
Aluminum hydroxide	Not established
Titanium dioxide	Not established
Cellulose	Oral LD50 Rat > 5 g/kg
	Inhalation LC50 Rat > 5800 mg/cu m/4H
	Dermal LD50 Rabbit > 2 g/kg
Vinyl acetate	Oral LD50 Rat = 2920 mg/kg
	Inhalation LC50 Rat = 11400 ml/cu m
	Dermal LD50 Rabbit = 2335 mg/kg
TOXICOLOGY SUMMARY:	No additional health information available.

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available

SECTION 13: DISPOSAL CONSIDERATIONS

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.

SECTION 14: TRANSPORTATION INFORMATION

Consult Bill of Lading for transportation information. DOT: NOT REGULATED IATA: NOT REGULATED

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS		
U.S. EPA TSCA:	This product is in compliance with the Toxic Substances Control Act's	
	Inventory requirements.	
CANADIAN CEPA DSL:	The components of this product are included on the DSL or are exempt from	
	DSL requirements.	
EUROPEAN EINECS:	As a result of the introduction of REACH into Europe, this product cannot be	
	imported into Europe unless the REACH requirements are met.	
If you need more information about the inventory status of this product call 651-236-5858.		

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at 651-236-5858 (USA) or 450-655-1306 x227 (Canada) to request an export review.

FEDERAL REPORTING

EPA SARA Title III Section 313

Unless listed below, this product does not	t contain toxic ch	emical(s) subject to	the reporting requirements of section
313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA			
has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.			
Chemical Name	CAS#	%	



Vinyl acetate

108-05-4 0.1 - 1

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System. D2A

STATE REPORTING This MSDS is not prepared for distribution in California.

SECTION 16: ADDITIONAL INFORMATION

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 0 FLAMMABILITY -- 0 REACTIVITY -- 0 See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B.Fuller Construction Products, Inc. from its suppliers, and because H.B.Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B.Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B.Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B.Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.