

REVISION DATE: 01-06-2012

SUPERSEDES: 11-16-2010

SECTION 1: CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

COMPANY INFORMATION H.B. Fuller Construction Products Inc. 1105 S. Frontenac Street Aurora, IL 60504 Phone: 1-800-552-6225

> Medical Emergency Phone Number (24 Hours): 1-888-853-1758 Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

| PRODUCT INFORMATION | |
|----------------------|--------------|
| PRODUCT NUMBER: | FOSTER 40-20 |
| PRODUCT DESCRIPTION: | Coating |
| PRODUCT IDENTIFIER: | 827566PM |

SECTION 2: HAZARDS IDENTIFICATION

| EMERGENCY OVERV | IEW |
|-----------------|------------|
| PHYSICAL STATE: | Liquid |
| COLOR: | White |
| ODOR: | Mild Sweet |
| Cancer hazard. | |

POTENTIAL HEALTH EFFECTS BY ROUTE OF ENTRY

EYE: Can cause minor irritation, tearing and reddening.

SKIN: Can cause minor skin irritation, defatting, and dermatitis.

INHALATION: Can cause minor respiratory irritation. Inhalation of dusts produced during cutting, grinding or sanding of this product may cause irritation of the respiratory tract.

Overexposure to barium dust/fume may cause baritosis. Overexposure to crystalline silica may cause silicosis.

This product contains one or more materials that may be hazardous when present as an airborne dust. During normal handling of the product, the material is encapsulated within the product and will not present an exposure risk. Once the product has reached its final state and is abraded or disturbed, dusting and exposure may occur.

INGESTION: Ingestion is not an anticipated route of exposure. No hazard in normal industrial use.

LONG-TERM (CHRONIC) HEALTH EFFECTS TARGET ORGAN(S): Lungs

REGULATED CARCINOGEN STATUS: Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH, or OSHA listed carcinogens. Titanium dioxide Crystalline silica

EXISTING HEALTH CONDITIONS AFFECTED BY EXPOSURE: Lung disease

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name | CAS # | PERCENT |
|--------------------|------------|---------|
| Aluminum hydroxide | 21645-51-2 | 10 - 30 |



| Barium compound | 13701-59-2 | 5 - 10 |
|--------------------|------------|---------|
| Calcium carbonate | 471-34-1 | 5 - 10 |
| Titanium dioxide | 13463-67-7 | 5 - 10 |
| Zinc oxide | 1314-13-2 | 1 - 5 |
| Mineral oil | 64742-46-7 | 0.1 - 1 |
| Crystalline silica | 14808-60-7 | 0.1 - 1 |

Unlisted ingredients are not 'hazardous' per the Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200) and/or are not found on the Canadian Workplace Hazardous Materials Information System ingredient disclosure list. See Section 8 for exposure limit guidelines.

SECTION 4: FIRST AID MEASURES

IF IN EYES: Use an eye wash to remove a chemical from your eye regardless of the level of hazard. Flush the affected eye for at least twenty minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical advice after flushing.

IF ON SKIN: Wash with soap and water. Get medical attention if irritation develops or persists.

IF VAPORS INHALED: Remove to fresh air. Call a physician if symptoms persist.

IF SWALLOWED: Do not induce vomiting. Seek medical attention if symptoms develop. Provide medical care provider with this MSDS. Induced vomiting may lead to aspiration of the material into the lungs potentially causing chemical pneumonitis that may be fatal.

SECTION 5: FIRE FIGHTING MEASURES

| FLASH POINT: | Non flammable |
|-------------------------------------|--|
| AUTOIGNITION TEMPERATURE: | Not established |
| LOWER EXPLOSIVE LIMIT (% in air): | Not established |
| UPPER EXPLOSIVE LIMIT (% in air): | Not established |
| EXTINGUISHING MEDIA: | Use water spray, foam, dry chemical or carbon dioxide. |
| UNUSUAL FIRE AND EXPLOSION HAZARDS: | |
| | when heated. Water spray may be used to cool the containers. |
| SPECIAL FIRE FIGHTING INSTRUCTIONS: | Persons exposed to products of combustion should wear self- |
| | contained breathing apparatus and full protective equipment. |
| HAZARDOUS COMBUSTION PRODUCTS: | Carbon dioxide, Carbon monoxide Metal fumes |
| | |

SECTION 6: ACCIDENTAL RELEASE MEASURES

| SPECIAL PROTECTION: | No adverse health effects expected from the clean-up of spilled material. |
|---------------------|--|
| | Follow personal protective equipment recommendations found in Section 8 |
| | of this MSDS. |
| CLEAN-UP: | Dike if necessary, contain spill with inert absorbent and transfer to containers |
| | for disposal. Keep spilled product out of sewers, watersheds, or water |
| | systems. |

Transport Emergency Phone Number (CHEMTREC): 1-800-424-9300

SECTION 7: HANDLING AND STORAGE

Handling: No special handling instructions due to toxicity.



Storage: Store in a cool, dry place. Consult the Technical Data Sheet for specific storage instructions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

| EYE PROTECTION: | Wear safety glasses when handling this product. |
|-------------------------|--|
| SKIN PROTECTION: | Avoid skin contact by wearing chemically resistant gloves. |
| GLOVES: | Not normally required. Use nitrile gloves if conditions warrant. |
| RESPIRATORY PROTECTION: | Respiratory protection may be required to avoid overexposure when handling this product. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms. Respirators should be selected by and used following requirements found in OSHA's respirator standard (29 CFR 1910.134). |
| VENTILATION: | Use local exhaust ventilation or other engineering controls to minimize exposures. |

EXPOSURE LIMITS:

| Chemical Name | ACGIH EXPOSURE LIMITS | OSHA PEL |
|--------------------|--|--|
| Aluminum hydroxide | Not established | Not established |
| Barium compound | Not established | Not established |
| Calcium carbonate | Not established | 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction) |
| Titanium dioxide | 10 mg/m3 TWA | 15 mg/m3 TWA (total dust) |
| Zinc oxide | 2 mg/m3 TWA (respirable fraction) 10 mg/m3 STEL (respirable fraction) | 5 mg/m3 TWA (fume); 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction) |
| Mineral oil | Not established | 5 mg/m3 TWA (as mist) |
| Crystalline silica | 0.025 mg/m3 TWA (respirable fraction) | ((250)/(%SiO2 + 5) mppcf TWA (respirable)); ((10)/(%SiO2 + 2) mg/m3 TWA (respirable)); ((30)/(%SiO2 + 2) mg/m3 TWA (total dust)) |

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| PHYSICAL STATE: | Liquid |
|----------------------------------|-----------------|
| COLOR: | White |
| ODOR: | Mild Sweet |
| ODOR THRESHOLD: | Not established |
| WEIGHT PER GALLON (lbs.): | 11.9 |
| SPECIFIC GRAVITY: | 1.43 |
| SOLIDS (% by weight): | 67.4 |
| pH: | Not established |
| FLASH POINT: | Non flammable |
| BOILING POINT (deg. C): | Not established |
| FREEZING/MELTING POINT (deg. C): | Not established |



| VAPOR PRESSURE (mm Hg): | Not esta |
|--|----------|
| VAPOR DENSITY: | Not esta |
| EVAPORATION RATE: | Not esta |
| OCTANOL/WATER COEFFICIENT: | Not esta |
| VOC, weight percent | 2.19 |
| VOC, EPA Method 24 (theoretically determined) | 31.4g/li |
| VOC, EPA Method 24, less water and exempt solvents | 35.3g/li |
| (theoretically determined) | |
| VOC, EPA Method 24 (analytically determined) | 41.94g/ |
| | |

Not established Not established Not established 2.19 31.4g/liter of material 35.3g/liter of material

41.94g/liter of material

SECTION 10: STABILITY AND REACTIVITY

STABILITY:Stable under normal conditions.CHEMICAL INCOMPATIBILITY:Not establishedHAZARDOUS POLYMERIZATION:Will not occur.HAZARDOUS DECOMPOSITION PRODUCTS:Carbon monoxide, carbon dioxide Metal fumes

SECTION 11: TOXICOLOGICAL INFORMATION

| COMPONENT | LD50/LC50 | |
|--------------------|---|--|
| Aluminum hydroxide | Not established | |
| Barium compound | Not established | |
| Calcium carbonate | Oral LD50 Rat = 6450 mg/kg | |
| Titanium dioxide | Not established | |
| Zinc oxide | Oral LD50 Mouse > 950 mg/kg Inhalation LC50 Mouse = 2500 mg/cu m (no duration specified) | |
| Mineral oil | Not established | |
| Crystalline silica | Not established | |
| TOXICOLOGY SUMMARY | Y: No additional health information available. | |

SECTION 12: ECOLOGICAL INFORMATION

OVERVIEW: No ecological information available

SECTION 13: DISPOSAL CONSIDERATIONS

To the best of our knowledge, this product does not meet the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. Solidify and dispose of in an approved landfill. Consult state, local or provincial authorities for more restrictive requirements.

SECTION 14: TRANSPORTATION INFORMATION

Consult Bill of Lading for transportation information.

DOT: NOT REGULATED

IATA: NOT REGULATED

SECTION 15: REGULATORY INFORMATION

INVENTORY STATUS

| U.S. EPA TSCA: | This product is in compliance with the Toxic Substances Control Act's |
|--------------------|--|
| | Inventory requirements. |
| CANADIAN CEPA DSL: | This product contains a component that is not on the DSL. If you are the |



importer of this product into Canada, contact H.B. Fuller for chemical tracking and notification information.

EUROPEAN EINECS:

ECS: As a result of the introduction of REACH into Europe, this product cannot be imported into Europe unless the REACH requirements are met.

If you need more information about the inventory status of this product call 651-236-5858.

This product may contain chemical substances that are regulated for export by various government agencies (such as the Environmental Protection Agency, the Bureau of Industry and Security, or the Drug Enforcement Administration, among others). Before exporting this product from the USA or Canada, we recommend you contact us at 651-236-5858 (USA) or 450-655-1306 x227 (Canada) to request an export review.

FEDERAL REPORTING

EPA SARA Title III Section 313

Unless listed below, this product does not contain toxic chemical(s) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR part 372. EPA has advised that when a percentage range is listed the midpoint may be used to fulfill reporting obligations.

| Chemical Name | CAS# | % |
|------------------|------------|--------|
| Barium compounds | 13701-59-2 | 5 - 10 |
| Zinc compounds | 1314-13-2 | 1 - 5 |

WHMIS STATUS: Unless listed below, this product is not controlled under the Canadian Workplace Hazardous Materials Information System.

D2A

STATE REPORTING

This MSDS is not prepared for distribution in California.

SECTION 16: ADDITIONAL INFORMATION

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

HMIS RATING: HEALTH -- 0 FLAMMABILITY -- 0 REACTIVITY -- 0 See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Prepared by: The Global Regulatory Department Phone: 651-236-5842

The information and recommendations set forth herein are believed to be accurate. Because some of the information is derived from information provided to H.B.Fuller Construction Products, Inc. from its suppliers, and because H.B.Fuller Construction Products, Inc. has no control over the conditions of handling and use, H.B.Fuller Construction Products, Inc. makes no warranty, expressed or implied, regarding the accuracy of the data or the results to be obtained from the use thereof. The information is supplied solely for your information and consideration, and H.B.Fuller Construction Products, Inc. assumes no responsibility for use or reliance thereon. It is the responsibility of the user of H.B.Fuller Construction Products, Inc. products to comply with all applicable federal, state and local laws and regulations.