



WEIGHT	SHIPPING WEIGHT	MODEL #	DROP D	ACTUAL LENGTH L
3.5 lb. 1.6 kg.	4.6 lb. 2.1 kg.	ADD101	12 inch .30 meter	14.7 .38
6.2 2.8	7.1 3.2	ADD102	24 .61	26.7 .68
8.9 4.1	11.3 5.1	ADD103	36 .91	38.7 .98
11.6 5.3	13.4 1.6	ADD104	48 1.22	50.7 1.28
14.4 4.6	17.8 8.1	ADD105	60 1.52	62.7 1.59
17.1 6.5	20.5 9.3	ADD106	72 1.83	74.7 1.90
19.8 9	25.8 8.9	ADD107	84 2.13	86.4 2.20
22.5 10.2	28.2 11.7	ADD108	96 2.44	98.7 2.51
25.2 11.5	35.8 16.3	ADD109	108 2.74	110.7 2.82
28 12.7	38.2 17.4	ADD110	120 3.01	122.7 3.12

Fixed Length Extension Columns are designed specifically for use with Peerless Multi Jumbo™ Display Mounts.

- * Other ceiling decouplers may be used if mounting to a structure other than an I-Beam. (Call Customer Service for more information.)
- ** Using different holes other than the ones that make the mount flush with I-Beam Clamp can increase the length in one inch increments.

Model	Application	Max. Load Capacity
DCS 400	structural or finished ceiling	1200 lbs (545 kg)
DCT 300	truss ceiling	1200 lbs (545 kg)
DCT 500	7" to 12" I-Beams	600 lbs (273 kg)
DCT 600	15" to 16" I-Beams 1.5" to 2" high	600 lbs (273 kg)
DCT 700	15" to 16" I-Beams 2.5" to 3" high	600 lbs (273 kg)

Architects specifications:

The extension column shall be a Peerless model ADD ____ . It shall be constructed of 1 1/2-11.5 NPT steel tubing and finished in scratch resistant black fused epoxy. It shall feature one notched end for safety locking. Assembly and installation shall be done according to the instructions provided by the manufacturer.



Peerless Industries, Inc. 3215 W. North Ave. Melrose Park, IL 60160
708-865-8870 800-865-2112 Fax 708-865-2941 www.peerlessindustries.com

TECHNICAL DATA SHEET

FIXED LENGTH EXTENSION COLUMNS FOR MULTI JUMBO™ DISPLAY SYSTEMS

ISSUED: 06-30-00 SHEET NO: 154-9503-2 02-11-03