

The Adjustable Extension Column for Jumbo Mounts is the most versatile choice for Jumbo Mount installations. Adjustability means that the exact position of the Jumbo Mount need not be predetermined. Length can easily be "fine tuned" at the time of installation and then locked into place.

The Adjustable Extension
Column is compatible
with all Peerless Jumbo
Mounts as well as some
Peerless Video Projector
Mounts. Many ceiling
plates are also available.
A ceiling plate or adaptor
with a decoupler is
recommended, especially
for longer Extension
Columns. Several models
are available. Adjustment
ranges are specified
(right).

ADJUSTABLE EXTENSION COLUMNS FOR JUMBO MOUNTS SPECIFICATIONS

Weight <i>lb (kg)</i>	Shipping Weight <i>lb (kg)</i>	Model#	Length (L) - adjustable at 1" increments in. (meter)
1.5 (.7)	2.8 (1.3)	ADJ006009	6 (.15) min. 9 (.23) max.
4.5 (2)	8 (3.6)	ADJ012018	12 (.30) min. 18 (.46) max.
5.5 (2.5)	7 (3.2)	ADJ018024	18 (.46) min. 24 (.61) max.
8.5 (3.9)	9.1 (4.1)	ADJ0203	24 (.61) min. 36 (.91) max.
11 (5)	14 (6.4)	ADJ0305	36 (.91) min. 60 (1.52) max.
15.5 (7)	16.6 (7.5)	ADJ0406	48 (1.22) min. 72 (1.83) max.
17 (7.7)	22 (10)	ADJ0507	60 (1.52) min. 84 (2.13) max.
18.5 (8.4)	23 (10.4)	ADJ0608	72 (1.83) min. 96 (2.44) max.
20 (9.1)	25 (11.3)	ADJ0709	84 (2.13) min. 108 (2.74) max.
21.5 (9.8)	27 (12.2)	ADJ0810	96 (2.44) min. 120 (3.05) max.
23 (10.4)	31.2 (14.2)	ADJ0911	108 (2.74) min. 132 (3.35) max.
24.5 (11.1)	34 (15.4)	ADJ1012	120 (3.05) min. 144 (3.66) max.


Adjustable Extension Column

Jumbo Mounts models JM630, JM640, JM640D, JM650, JM650D, JM655, JM660, JM665, JM670, JM675



This product must be installed by a qualified, professional installer.

MAXIMUM LOAD CAPACITY: 600 lb (273 kg)



The "tube in tube" design of the Adjustable Extension Column allows it to be adjusted, within its specified range, at 1 inch (25 mm) increments. The bolt and lock nut provided securely locks the two tubes together at the desired length.

Shipping weight based on single unit shipment. Per unit shipping weight may be less for bulk orders.

Architects specifications:

The Adjustable Extension Column shall be a Peerless model ADJ______. It shall offer a _____ inch range of height adjustment at 1" increments. It shall be constructed of steel tubing and finished in black fused epoxy. Assembly and installation shall be done according to the instructions provided by the manufacturer.

TECHNICAL DATA SHEET ADJUSTABLE LENGTH EXTENSION COLUMN

Peerless Industries, Inc.

3215 W. North Ave. phone: (708) 865-8870 Melrose Park, IL 60160 fax: (708) 865-2941

www.peerlessindustries.com

ISSUED: 7-15-94 SHEET NO:154-9501-3

9501-3 8-18-03

page 1 of 1